## **SIEMENS**

## Data sheet

6GK7243-1EX01-0XE0

product type designation

## CP 243-1

\*\*\*\*\*\*\*\* spare part \*\*\*\*\*\*\* communications processor CP 243-1 for connection of SIMATIC S7-22X to Industrial Ethernet; FTP client communication; HTTP server; FTP server; Email client



transfer rate	
transfer rate	
• at the 1st interface	10 100 Mbit/s
interfaces	
number of interfaces / acc. to Industrial Ethernet	1
number of electrical connections	
• at the 1st interface / acc. to Industrial Ethernet	1
• for power supply	1
type of electrical connection	
• at the 1st interface / acc. to Industrial Ethernet	RJ45 port
type of electrical connection	
• for power supply	3-pole terminal block
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
supply voltage / external	24 V
supply voltage / external / at DC / rated value	24 V

relative positive tolerance / at DC / at 24 V	20 %
relative negative tolerance / at DC / at 24 V	15 %
consumed current	
• from backplane bus / at DC / at 5 V / typical	0.06 A
<ul> <li>from external supply voltage / at DC / at 24 V / typical</li> </ul>	0.053 A
<ul> <li>from external supply voltage / at DC / at 24 V / maximum</li> </ul>	0.06 A
power loss [W]	1.5 W
ambient conditions	
ambient temperature	
<ul> <li>for vertical installation / during operation</li> </ul>	0 45 °C
<ul> <li>for horizontally arranged busbars / during operation</li> </ul>	0 55 °C
during storage	-40 +70 °C
during transport	-40 +70 °C
relative humidity	
<ul> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-200 double width
width	71.2 mm
height	80 mm
depth	62 mm
net weight	0.15 kg
product features, product functions, product components / general	
number of units	
• per CPU / maximum	1
• note	-
performance data / S7 communication	
number of possible connections / for S7	
communication	
• maximum	8
• with PG connections / maximum	1
• with PG/OP connections / maximum	8
performance data / IT functions	
number of possible connections	
• as client / by means of FTP / maximum	1
number of possible connections	
<ul><li>as server / by means of HTTP / maximum</li></ul>	4

as email client / maximum	1	
number of emails with 1024 characters / of email	32	
client / maximum		
number of access authorizations / of access	8	
protection		
storage capacity / of the user memory		
<ul> <li>as flash memory file system</li> </ul>	8 Mibyte	
number of possible write cycles / of the flash memory	100000	
cells		
performance data / telecontrol		
protocol / is supported		
• TCP/IP	Yes	
product functions / management, configuration, engineering		
product function / MIB support	No	
protocol / is supported		
• SNMP v1	No	
configuration software		
• required	STEP 7-Micro/WIN Version V4.0 SP8 or higher	
product functions / diagnostics		
product function / web-based diagnostics	Yes	
product functions / switch		
product feature / switch	No	
further information / internet-Links		
Internet-Link		
• to website: Industrial communication	http://www.siemens.com/simatic-net	
• to website: Industry Mall	https://mall.industry.siemens.com	
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter	
• to website: Image database	http://automation.siemens.com/bilddb	
• to website: CAx-Download-Manager	http://www.siemens.com/cax	
• to website: Industry Online Support	https://support.industry.siemens.com	
security information		

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

11/20/2020