

Product type designation

CP 1243-1 IEC
COMMUNICATIONS PROCESSOR CP 1243-1 IEC FOR
CONNECTING SIMATIC S7-1200 TO CONTROL CENTER W.
PROTOCOL IEC60870-5-104



Transmission rate

Transfer rate

- at the 1st interface 10 ... 100 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

1

Number of electrical connections

- at the 1st interface / acc. to Industrial Ethernet 1
- for power supply 0

Type of electrical connection

- at the 1st interface / acc. to Industrial Ethernet RJ45 port

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Consumed current

- from backplane bus / at DC / at 5 V / typical 0.25 A

Active power loss

1.25 W

Permitted ambient conditions

Ambient temperature	
• for vertical installation / during operation	-20 ... +60 °C
• for horizontally arranged busbars / during operation	-20 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-1200 single width
Width	30 mm
Height	110 mm
Depth	75 mm
Net weight	0.122 kg
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes

Product properties, functions, components / general

Number of units	
• per CPU / maximum	3

Performance data / S7 communication

Number of possible connections / for S7 communication	
• Note	like CPU

Performance data / IT functions

Number of possible connections	
• as e-mail client / maximum	1

Performance data / telecontrol

Suitability for use	
• Node station	No
• substation	Yes
• TIM control center	No
Control center connection	control center with IEC 60870-5 function
Control center connection / by means of a permanent connection	supported
Control center connection / Note	Connection to Scada system using IEC 60870-5
Protocol / is supported	
• DNP3	No
• IEC 60870-5	Yes

Product function / data buffering if connection is aborted	Yes
• Note	64,000 values
Number of data points per station / maximum	200

Performance data / Teleservice

Diagnostics function / online diagnostics with SIMATIC STEP 7	Yes
Product function	
• program download with SIMATIC STEP 7	Yes
• Remote firmware update	Yes

Product functions / management, configuration

Configuration software	
• required	STEP 7 Basic/Professional V13 (TIA Portal) or higher

Product functions / Time

Protocol / is supported / NTP	No
time synchronization	
• from control center	Yes

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

12.09.2015