



COMMUNICATIONSPROCESSOR CP343-1 ERPC FOR CONNECTING SIMATIC S7-300 CPU TO INDUSTRIAL ETHERNET AND TO VARIOUS DATABASES. FUNCTIONS: TCP/UDP, S7-COMM, OPEN COMM. WITH AND WITHOUT RFC 1006, MULTICAST, WEBSERVER, TIME VIA SIMATIC PROCESS OR NTP, ACCESS PROTECTION VIA IP-ACCESS LIST, SNMP, DHCP, C-PLUG, GIGABIT-SS 1X RJ45 (10/100/1000 MBIT);

Transmission rate

Transfer rate / at the interface 1	10 ... 1000 Mbit/s
------------------------------------	--------------------

Interfaces

Number of electrical connections	
• at interface 1 / in accordance with Industrial Ethernet	1
• for power supply	1
design of the removable storage / C-PLUG	Yes

Supply voltage, current consumption, power loss

Type of voltage / of supply voltage	DC
Supply voltage	
• 1 / from backplane bus	5 V
• external	24 V
Relative positive tolerance / at 24 V / with DC	20 %
Relative negative tolerance / at 24 V / with DC	15 %
Consumed current	
• from backplane bus / at 5 V / for DC / Typical	0.3 A
• from external supply voltage / at 24 V / with DC	
• typical	0.16 A
• maximum	0.6 A
Resistive loss	14.7 W

Permitted ambient conditions

Ambient temperature	
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity	
• at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP20
Design, dimensions and weight	
Width	80 mm
Height	125 mm
Depth	120 mm
Net weight	0.8 kg
Performance data / open communication	
Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	8
Data volume	
• as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
• as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
• as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum	2 Kibyte
Number of Multicast stations	8
Performance data / S7 communication	
Number of possible connections / for S7 communication	
• maximum	8
Performance data / multi-protocol mode	
Number of active connections / with multiprotocol mode	32
Performance data / ERPC functions	
Number of possible connections / for communication with ERP or MES stations / maximum	8
Number of possible logical triggers / per CP / maximum	8
Number of configurable ERPC symbols for database access	
• per CPU / maximum	2000
• per logical trigger / maximum	255
Data volume / as user data and header information per logical trigger	8 Kibyte
Product functions / management, configuration	
Product function / MIB support	Yes
Protocol / is supported	
• SNMP v1	Yes
• DCP	Yes
• LLDP	Yes

Identification & maintenance	
• I&M0 - device-specific information	Yes
• I&M1 - plant identification/location name	Yes
Product functions / Diagnosis	
Product function / Web-based diagnostics	Yes
Product functions / Redundancy	
Product function / Ring redundancy	No
Product functions / Security	
Product function	
• ACL - IP-based	Yes
• switchoff of non-required services	Yes
• blocking of communication via physical ports	Yes
• log file for unauthorized access	No
Product functions / Time	
Product function	
• SICLOCK support	Yes
• pass on time synchronization	Yes
Protocol / is supported / NTP	Yes
letzte Änderung:	Jul 17, 2012