

Product type designation

Antenna ANT 3

RF300/RF200 antenna ANT 3 for Connection to RF250R RF350R and RF350M IP67. -25 to +70 °C, Dimensions 50x 28x 10 mm



Suitability for operation	RF250R / RF350R / RF350M
Radio frequencies	
Transmission frequency / Rated value	13.56 MHz
Electrical data	
Type of electrical connection / of the antenna	M8, 4-pin
Design of plug-in connection	female
Mechanical data	
Material	PA6 V0
Color	black
Tightening torque / of the screw for securing the equipment / maximum	1 N·m
Mounting distance • relating to metal surfaces / recommended / minimum	0 m
Ambient conditions	
Ambient temperature • during operation	-25 ... +70 °C

• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Protection class IP	IP67
Shock resistance	according to EN 60721-3-7 Class 7M2
Shock acceleration	500 m/s ²
Vibrational acceleration	200 m/s ²

Design, dimensions and weights	
Width	28 mm
Height	50 mm
Depth	10 mm
Net weight	35 g
Mounting type	2 x M4 screws

Standards, specifications, approvals	
Certificate of suitability	CE, FCC, IC, cULus
Certificate of suitability • IECEx	Yes

accessories	
accessories	Antenna cable

Further information / Internet-Links	
Internet-Link • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager • to website: Industry Online Support	https://support.industry.siemens.com/cs/ww/en/view/67384964 http://www.siemens.com/ident/rfid https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
last modified:	01/09/2020