SIEMENS

Data sheet 6GT2503-1AA00

Product type designation

Reader/Antenna SLG U92 with Li-Ion accumulator MOBY U ANTENNA STG U FOR HANDHELD TERMINAL STG U; WITH RECHARGEABLE BATTERY, W/O CHARGER STG U, W/O DESCRIPTION, W/O SOFTWARE



Figure similar

Suitability for operation	MOBY U, to be connected to hand terminal Psion workabout mx
Wireless frequencies	
Operating frequency	2400 2483.5 MHz
Equivalent isotropically radiated power	
• minimum	0.7 mW
• maximum	0.7 mW
Electrical data	
Range / maximum	3 m; Range adjustable in reader in steps of 0.5 m

Electrical data	
Range / maximum	3 m; Range adjustable in reader in steps of 0.5 m
Protocol / with radio transmission	ISO 18000-4
Transfer rate / with radio transmission / maximum	384 kbit/s
Product feature / multitag-capable	Yes
Polarization	circular
Transfer rate / at the point-to-point connection / serial	115.2 kbit/s
/ maximum	
Transmission time / for user data	
for write access / per byte / typical	0.13 ms

• for read access / per byte / typical	0.21 ms	
Interfaces		
Standard for interfaces / for communication	RS232	
Type of electrical connection		
• for supply voltage	4-pin female connector for connecting to charger	
• for communications interface	integrated sub-D connector, 9 pin	
Mechanical data		
Material	Valox 357	
Color	anthracite	
Supply voltage, current consumption, power loss		
Supply voltage		
• at DC / Rated value	12 V	
Consumed current / at DC / at 24 V		
• typical	1.225 A	
Permitted ambient conditions		
Ambient temperature		
during operation	-20 +60 °C	
during storage	-25 +70 °C	
during transport	-25 +70 °C	
Protection class IP	IP54	
Design, dimensions and weight		
Width	235 mm	
Height	93 mm	
Depth	282 mm	
Net weight	1 kg	
Mounting type	mounting adaptor for Psion workabout mx	
Product properties, functions, components / genera		
Display version	-	
Product feature / silicon-free	Yes	
Standards, specifications, approvals		
Certificate of suitability	RF: EN 300440-2, SAR: EN 50371, safety: EN 60950-1, EMC: EN	
	301489-01, EN 301489-03, ENV 50204, FCC Part 15C (USA), cULus, safe for heart pacemakers	
MTBF	68 y	
MIDI	00 y	
Accessories		
accessories	replacement accu: Lilon-Accu-Pack (7,2 V 1,8 Ah)	
Further Information / Internet Links		
Internet-Link		

• to website: Selector SIMATIC NET

SELECTION TOOL

• to website: Industrial communication

• to website: Industry Mall

• to website: Information and Download Center

• to website: Image database

• to website: CAx Download Manager

• to website: Industry Online Support

last modified:

https://support.industry.siemens.com/cs/ww/en/view/67384964

http://www.siemens.com/ident/rfid

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

10/17/2016