

Product type designation
Product description

Universal support MDS U589
Support for mounting heat-resistant transponders on the body using customer-specific adapters
RF300 / MOBY U UNIVERSAL MOUNTING ACCESS. FOR HEAT-PROOF DATA MEMORY, MDS U589



Figure similar

Suitability for use	The support is attached via 2 M8 screws in the application
Mechanical data	
Material	Stainless steel
Color	anthracite
Permitted ambient conditions	
Ambient temperature	
• during operation	-40 ... +220 °C
• during storage	-40 ... +220 °C
• during transport	-40 ... +220 °C
Design, dimensions and weight	
Height	41 mm
Diameter	129.5 mm
Further Information / Internet Links	
Internet-Link	

- to website: TIA Selection Tool
- to website: Selector SIMATIC NET
SELECTION TOOL
- to the website: IWLAN
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

last modified:

<http://www.siemens.com/tia-selection-tool>
<https://support.industry.siemens.com/WW/view/en/67384964>

<http://www.siemens.com/iwlan>
<http://www.siemens.com/ident/rfid>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

10/19/2016