

Product-type designation	
	
MDS D324 transponder	
TRANSPONDER MDS D324 FOR RF200/ RF300 ISO/ MOBY D BUTTON ISO 15693 CHIP TYPE,INFINEON SRF 55V10P, 992 BYTE USER MEMORY; 27 X 4 MM (DXH); -25 UP TO +125 DGR; MINIMAL ORDER QUANTITY 20 PCS	
Suitability for installation	RF200, RF300, MOBY D
Wireless frequencies	
Operating frequency / rated value	13.56 MHz
Electrical data	
Range	
• maximum	280 mm
Protocol / for radio transmission	ISO 15693
Transfer rate / with radio transmission / maximum	26.5 kbit/s
Product property / multitag-capable	Yes
Product component / Buffer battery	No
Memory	
Type of memory	EEPROM
Memory capacity / of user memory	992 byte
Type of memory organization	UID (fixed code) 8 bytes, user memory 992 bytes, configuration memory 24 bytes
Number of read cycles / at ambient temperature < 40 °C / maximum	1000000000000000
Number of write cycles / at ambient temperature < 40 °C / maximum	1000000
Data retention time / at ambient temperature < 40°C / at least	10 a
Property of memory	Block-by-block write protection of the user memory
Mechanical data	

Material	Epoxy resin
Color	black
Tightening torque / of screw for mounting the equipment / maximum	1 N·m
Mounting distance / for metal surfaces / recommended / minimum	25 mm
Permitted ambient conditions	
Ambient temperature	
• during read/write access	-25 ... +125 °C
• outside the read/write area	-40 ... +150 °C
• during storage	-40 +150 °C
Protection class IP	IP67
Resistance against shock	According to DIN EN 60721-3-7 Class 7 M3
Resistance against shock	1000 m/s ²
Resistance against vibration	200 m/s ²
Design, dimensions and weight	
Height	4 mm
Diameter	27 mm
Net weight	5 g
Product properties, functions, components / general	
Product feature / silicon-free	Yes
Product property / printable	No
Standards, specifications, approvals	
MTBF	171 a
Accessories	Mounting support and spacer
letzte Änderung:	Jul 21, 2014