

Data sheet

6GT2690-0AH00

Product type designation

Product description

quick-change chuck MDS D139, D339

Support for mounting heat-resistant transponders with 20 mm distance to metal

MOBY D / RF300 ISO QUICK CHANGE HOLDER STAINLESS STEEL FOR MDS D139 AND MDS D339; DIAMETER 22 MM

HEIGHT 48 MM; MOUNTING WITH NUT M8 PACKAGING UNIT 10 PCS



Suitability for use

The support is mounted via M8 nuts, whereas the transponder is held by a splint. The splint allows the transponder to be quickly removed from the support.

Mechanical data

Material	Stainless steel
Color	metallic

Permitted ambient conditions

Ambient temperature	
• during operation	-40 ... +220 °C
• during storage	-40 ... +220 °C
• during transport	-40 ... +220 °C

Design, dimensions and weight

Height	60 mm
Diameter	22 mm
Net weight	80 g

Further Information / Internet Links

Internet-Link

- to website: TIA Selection Tool
- to website: Selector SIMATIC NET
SELECTION TOOL
- to the website: IWLAN
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>

<https://support.industry.siemens.com/WW/view/en/67384964>

<http://www.siemens.com/iwlan>

<http://www.siemens.com/ident/rfid>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

10/12/2016