

Data sheet

6GT2690-0AH10

product type designation

product description

quick-change chuck MDS D139, D339

Support for mounting heat-resistant transponders with 20 mm distance to metal

MOBY D/RF300 ISO Quick change holder Stainless steel for MDS D139 and MDS D339; With M10 female thread; Packing unit: 10 units



suitability for use

The support is mounted using an M10 screw, whereas the transponder is held by a splint. The splint allows the transponder to be quickly removed from the support.

mechanical data

material	Stainless steel
color	metallic

ambient conditions

ambient temperature	
• during operation	-40 ... +220 °C
• during storage	-40 ... +220 °C
• during transport	-40 ... +220 °C

design, dimensions and weights

height	48 mm
diameter	22 mm
net weight	60 g

further information / internet-Links

Internet-Link

- to website: TIA Selection Tool
- to the website: IWLAN
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Selection guide for cables and connectors
- to website: Image database
- to website: CAX-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>
<http://www.siemens.com/iwlan>
<http://www.siemens.com/ident/rfid>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<https://sie.ag/2QdlxcP>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

5/20/2021