

Data sheet

6GT2800-1CA00

Product type designation

RF320T transponder

SIMATIC RF300 TRANSPONDER RF320T BUTTON, 20 BYTE
EEPROM, IP 67, -25 TO +125 DEGR/C, D=27 MM X 4 MM MIN.
ORDER QUANTITY 20 PCS

Wireless frequencies

Operating frequency / Rated value	13.56 MHz
-----------------------------------	-----------

Electrical data

Range / maximum	60 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
Protocol / with radio transmission	RF300-specific
Transfer rate / with radio transmission / maximum	106 kbit/s
Product feature / multitag-capable	Yes
Product component / Backup battery	No

Memory

Type of memory	EEPROM
Storage capacity / of the user memory	20 byte
Type of memory organization	UID (fixed code) 4 bytes, user memory 20 bytes,
Number of read cycles / at ambient temperature < 40 °C / maximum	1000000000000000
Number of write cycles / at ambient temperature < 40 °C / maximum	1000000
Data retention time / at ambient temperature < 40 °C / not less than	10 y
Property of memory	Block-by-block write protection of the user memory

Mechanical data

Material	Epoxy resin
Color	black
Mounting distance / relating to metal surfaces / recommended / minimum	20 mm

Permitted ambient conditions

Ambient temperature	
• during read/write access	-25 ... +125 °C
• outside the read/write area	-40 ... +140 °C
• during storage	-40 ... +140 °C
Protection class IP	IP67 / IPx9K
Shock resistance	According to DIN EN 60721-3-7 Class 7 M3
Shock acceleration	1000 m/s ²
Vibrational acceleration	200 m/s ²

Design, dimensions and weight	
Height	4 mm
Diameter	27 mm
Net weight	5 g
Mounting type	M3 screw, gluing
Product properties, functions, components / general	
Product feature	
• silicon-free	Yes
• printable	No
Standards, specifications, approvals	
MTBF	1800 y
Accessories	
accessories	Mounting support and spacer
Further Information / Internet Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	https://support.industry.siemens.com/cs/ww/en/view/67384964
• to website: Industrial communication	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
last modified:	02/04/2017