

Product type designation

RF360T transponder

SIMATIC RF300 TRANSPONDER RF360T EPOXY-CARD, 8 KBYTE FRAM, IP 67, -25 UP TO +70 DEGR/C, 85 X 54 X 2.5 MM MIN.
ORDER QUANTITY 10 PCS



Wireless frequencies

Operating frequency / Rated value	13.56 MHz
-----------------------------------	-----------

Electrical data

Range / maximum	150 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
Protocol / with radio transmission	RF300-specific
Transfer rate / with radio transmission / maximum	106 kbit/s
Product feature / multitag-capable	Yes
Product component / Backup battery	No

Memory

Type of memory	FRAM/EEPROM
Storage capacity / of the user memory	8189 byte
Type of memory organization	UID (fixed code) 4 bytes, user memory 8189 bytes, OTP memory 20 bytes
Number of read cycles / at ambient temperature < 40 °C / maximum	10000000000
Number of write cycles / at ambient temperature < 40 °C / maximum	10000000000

Data retention time / at ambient temperature < 40 °C / not less than	10 y
Property of memory	Block-by-block write protection of the OTP memory
Mechanical data	
Material	Epoxy resin
Color	anthracite
Mounting distance / relating to metal surfaces / recommended / minimum	20 mm
Permitted ambient conditions	
Ambient temperature	
• during read/write access	-25 ... +75 °C
• outside the read/write area	-40 ... +85 °C
• during storage	-40 ... +85 °C
Protection class IP	IP67
Shock resistance	According to DIN EN 60721-3-7 Class 7 M3
Shock acceleration	500 m/s ²
Vibrational acceleration	200 m/s ²
Resistance to mechanical stress	Continuous torsion and bending stress not permissible
Design, dimensions and weight	
Width	55 mm
Height	2.5 mm
Depth	86 mm
Net weight	25 g
Mounting type	2 x M3 screws, mounting bag (see accessories)
Product properties, functions, components / general	
Product feature	
• silicon-free	Yes
• printable	No
Standards, specifications, approvals	
MTBF	1200 y
Accessories	
accessories	Fixing strap, spacer
Further Information / Internet Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	https://support.industry.siemens.com/cs/ww/en/view/67384964
• to website: Industrial communication	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb

- to website: CAx Download Manager
- to website: Industry Online Support

last modified:

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

06/21/2017