

Product type designation

Reader RF680R CMIIT

SIMATIC RF600 READER RF680R CMIIT; INTERFACES:
ETHERNET M12, PROFINET M12, 4 ANTENNAS, 4 DIG. INPUTS/
4 DIG. OUTPUTS, 24 V DC; IP65; -25 UP TO +55 DEG/C; W/O
ACCESSORIES AND ANTENNAS



Wireless frequencies

Operating frequency	920 ... 925 MHz
Transmit power	3 ... 2000 mW
Effective radiant power	
• for each external antenna / maximum	2000 mW

Electrical data

Range / maximum	8 m
Transfer rate / with radio transmission / maximum	400 kbit/s
Product feature / multitag-capable	Yes
Transmission time / for user data	
• for write access / per byte / typical	2 ms
• for read access / per byte / typical	0.15 ms

Interfaces

Number of external antennas	4
Type of electrical connection	
• for external antenna(s)	RP-TNC
• for supply voltage	M12, 8-pin, connector

• for communications interface • at the digital inputs/outputs	2 x M12 4-pin D-coded, M12 8-pin (RS422) M12, 12-pin, female connector
Number of digital inputs	4
Number of digital outputs	4

Mechanical data	
Material	Aluminum, Pocan
Color	silver, TI-Grey
Mounting distance / relating to metal surfaces / recommended / minimum	0 mm

Supply voltage, current consumption, power loss	
Supply voltage	
• at DC / Rated value • at DC	24 V 20 ... 30 V
Consumed current / at DC / at 24 V	
• typical • maximum	0.38 A 2 A

Permitted ambient conditions	
Ambient temperature	
• during operation • during storage • during transport	-25 ... +55 °C -40 ... +85 °C -40 ... +85 °C
Ambient condition / for operation	With operating temperature below -20 °C: Warming-up time at least 10 minutes
Protection class IP	IP65
Shock resistance	EN 60068-2-27, EN 60068-2-6
Shock acceleration	500 m/s ²
Vibrational acceleration	200 m/s ²

Design, dimensions and weight	
Width	258 mm
Height	258 mm
Depth	80 mm
Net weight	2.4 kg
Mounting type	Vesa 100 with 4 x M4 screws, top-hat rail 35 mm, profile rail S7-300, S7-1200 or S7-1500
Wire length	
• of antenna cable / minimum • of antenna cable / maximum	1 m 40 m

Product properties, functions, components / general	
Display version	two LED rows with 8 and 9 LEDs
Product feature / silicon-free	Yes

Standards, specifications, approvals	
--------------------------------------	--

Certificate of suitability	RaWireless according to CMIIT
MTBF	28 y

Accessories

accessories	up to 4 external antennas, set for mounting on top-hat rail or profile rail
-------------	---

Further Information / Internet Links

Internet-Link

- | | |
|--|---|
| <ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager • to website: Industry Online Support | https://support.industry.siemens.com/cs/ww/en/view/67384964

http://www.siemens.com/ident/rfid
https://mall.industry.siemens.com
http://www.siemens.com/industry/infocenter
http://automation.siemens.com/bilddb
http://www.siemens.com/cax
https://support.industry.siemens.com |
|--|---|

last modified: 11/28/2017