

Product-type designation	
	
Antenna RF620A, ETSI SIMATIC RF600 ANTENNA RF620A ; ETSI FREQUENCY 865-868 EU LINEAR IP 67, -20 UP TO +70 DGR/C, WITH 30CM CONNECT. CABLE	
Suitability for installation	SIMATIC RF600
Transmission frequency	
• initial value	865 MHz
• end value	868 MHz
Electrical data	
Impedance	50 Ω
Polarization	Linear
Antenna gain compared to spherical radiator	
• with linear radiation	-5 dB
Standing wave ratio VSWR / maximum	2
Beam angle of antenna	
• horizontal	100 °
• vertical	75 °
Mechanical data	
Color	Pastel turquoise
Tightening torque / of screw for mounting the equipment / maximum	2 N·m
Mounting distance / for metal surfaces / recommended / minimum	0 m
Design of the plug-in connection	male
Permitted ambient conditions	
Ambient temperature	

• during operating	-20 ... +70 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Protection class IP	IP67
Resistance against shock	according to EN 60068-2-27
Resistance against shock	500 m/s ²
Resistance against vibration	200 m/s ²
Design, dimensions and weight	
Width	75 mm
Height	75 mm
Depth	20 mm
Net weight	100 g
Mounting type	2 screws M5
Product properties, functions, components / general	
Product feature / silicon-free	Yes
Standards, specifications, approvals	
Verification of suitability	CE (ETSI EN 302208)
Further Information / Internet Links	
Internet-Link	
• to website: Industry Mall	https://www.siemens.com/industrymall
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	http://support.automation.siemens.com
letzte Änderung:	Aug 9, 2014