

Product type designation

RF650M ETSI mobile hand-held terminal

SIMATIC RF600 Mobile Reader RF650M ETSI, Basic device incl. rechargeable battery, incl. charging unit, UHF, ISO 18000-6C, WLAN 802.11a/b/g/n, MS-Windows CE 6.0



Suitability for operation	RF600 transponder
Range	2500 mm
Wireless frequencies	
Operating frequency	865.6 ... 867.6 MHz
Effective radiant power	500 mW
Electrical data	
Protocol / with radio transmission	EPCglobal Class 1 Gen 2 / ISO 18000-6C
Product feature / multitag-capable	Yes
Polarization	Linear horizontal, vertical, automatic
Supply voltage, current consumption, power loss	
Type of current supply	Battery operation or mains operation
Type of battery	Li-Polymer accumulator, replaceable
Battery capacity	2.26 A·h
Operating period / with standard battery / typical	9 h
Permitted ambient conditions	
Ambient temperature	-20 ... +55 °C
• during operation	

• during storage	-20 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Height of fall / maximum	1.5 m
Protection class IP	IP54

Design, dimensions and weight

Width	60 mm
Height	147 mm
Depth	39 mm
Net weight	0.24 kg

Product properties, functions, components / general

Design of the display	QVGA color touch screen 2.2 inch, 240 x 320 pixels
Operator element version	Alphanumeric
Design of acoustic signaling element	Speakers
Design of the interface	WLAN, USB and Ethernet via charging station
Storage capacity	
• of the RAM	256 Mibyte
• of the data and program memory	288 Mibyte
• of the data memory / can be used	256 Mibyte

Product functions / management, configuration

Operating system / pre-installed	Windows Embedded CE 6.0
Product function / of the software	Record, process, search of ISO 18000-6C transponder
Type of programming	Programming with MS Visual Studio 2008 API for several programming languages available

Standards, specifications, approvals

Certificate of suitability	EMC: EN 55022, EN 301 489, safety: EN 60950, RF: EN 302 208
MTBF	43 y

Accessories

accessories	Charging/docking station with USB- and Ethernet interface, changeable accumulator Li-Po 2260 mAh / 3,7 V, also included: charging device 100-240 V
-------------	--

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	https://support.industry.siemens.com/cs/ww/en/view/67384964
• to website: Industrial communication	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified:

08/27/2019