

Product-type designation	
	
RF240R reader SIMATIC RF200 READER RF240R; RS232-INTERFACE (3964R); IP 67, -25 UP TO +70 DGR/C; 50 X 50 X 30 MM; WITH INTEGRATED ANTENNA.	
Wireless frequencies	
Operating frequency / rated value	13.56 MHz
Electrical data	
Range / maximum	65 mm
Protocol / for radio transmission	ISO 15693, ISO 18000-3
Transfer rate / with radio transmission / maximum	26.5 kbit/s
Product property / multitag-capable	No
Transmission rate / at point-to-point connection / serial / maximum	115.2 kbit/s
Transmission time / for user data	
• for write access / per byte / typical	0.6 ms
• for read access / per byte / typical	0.6 ms
Interfaces	
Design of the electrical connection	M12, 8-pin
Standard for interfaces / for communication	RS232
Mechanical data	
Material	PA6.6
Color	Anthracite
Tightening torque / of screw for mounting the equipment / maximum	1.5 N·m
Mounting distance / for metal surfaces / recommended / minimum	0 mm

Supply voltage, current consumption, power loss	
Supply voltage / for DC	
• rated value	24 V
• minimum	20.4 V
• maximum	28.8 V
Consumed current / At 24 V / with DC	
• typical	0.05 A
Permitted ambient conditions	
Ambient temperature	
• during operating	-20 ... +70 °C
• during storage	-25 ... +80 °C
• during transport	-25 ... +80 °C
Protection class IP	IP67
Resistance against shock	EN 60721-3-7, Class 7 M2
Resistance against shock	500 m/s ²
Resistance against vibration	200 m/s ²
Design, dimensions and weight	
Width	50 mm
Height	30 mm
Depth	50 mm
Net weight	0.06 kg
Mounting type	2 x M5 screws
Cable length	
• with RS 232 interface / maximum	30 m
Product properties, functions, components / general	
Type of display	3-color LED
Product feature / silicon-free	Yes
Standards, specifications, approvals	
Verification of suitability	Wireless according to R&TTE guidelines EN300 330 and EN 301489, FCC, UL/CSA
MTBF	430 a
letzte Änderung:	Aug 4, 2014