SIEMENS

Data sheet 6GT2831-6AA60

product type designation



RF1060R USB reader

SIMATIC RF1000 Access control reader RF1060R; ISO 14443 A/B Mifare, ISO15693 USB port; IP65 front, -25 to +55 $^{\circ}$ C; 90 x 62 x 25 mm LxWxH; with integrated antenna, incl. 1.8 m USB connecting cable .

suitability for operation

ISO 15693 and ISO 14443 A/B transponder, for connecting to PC and control systems

radio frequencies	
operating frequency / rated value	13.56 MHz
range / maximum	0.03 m; Range is dependent on transponder type: observe http://support.automation.siemens.com/WW/view/en/67384964
protocol / with radio transmission	ISO 15693, ISO 14443 A/B, Felica, NXP NTAG21x, HID iClass
transfer rate / with radio transmission / maximum	424 kbit/s
product feature / multitag-capable	Yes
nterfaces	
standard for interfaces / for communication	USB 2.0
type of electrical connection	1.8 m connecting cable with USB 2.0 type A connector
mechanical data	
material	PC-GF
color	Ti gray
mounting distance / relating to metal surfaces / recommended / minimum	0 mm
supply voltage, current consumption, power loss	
supply voltage / at DC	
rated value	5 V
•	4.5 5.25 V
consumed current / at DC	
at 5 V / typical	0.15 A
• at 5 V / maximum	0.3 A
ambient conditions	
ambient temperature	
 during operation 	-25 +55 °C
during storage	-25 +55 °C
during transport	-25 +55 °C
protection class IP	IP65; on front after cabinet installation, IP20 rear
shock resistance	EN 60721-3-7 Class 7 M2
shock acceleration	300 m/s²
vibrational acceleration	50 m/s ²
design, dimensions and weights	
width	90 mm
height	62 mm
depth	23.5 mm
net weight	0.12 kg
fastening method	4 M4 screws for cabinet installation
product features, product functions, product components / gen	eral

display version	3-color LED
product feature / silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	Radio according to R&TTE guidelines EN300 330 and EN 301489, FCC, cULus
certificate of suitability	
• IECEx	No
ccessories	
accessories	card holder, USB cable 0.5 m, table/wall box, clean room cover,
urther information / internet links	
internet link	
 to website: Image database 	https://www.automation.siemens.com/bilddb
 to website: Industry Online Support 	https://support.industry.siemens.com
ecurity information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)
Approvals / Certificates General Product Approval	Radio Equipment Type Approval Certificate
CB (€ EG-Konf.	Industry Canada (IC) Miscellaneous FCC

last modified:

4/16/2024

