SIEMENS

Data sheet 6GT2891-4MH50

Product type designation

Product description

Cable for IO-Link, M12 / M12

Sensor cable (3-core)

SIMATIC RF IO-Link connecting cable, pre-assembled, between IO-Link master and reader, both ends M12 4-pole 3-core cable, PUR, Length 5m



Figure similar

Suitability for use	Plug-in cable for connecting an IO-Link device to an IO-Link master
Cable designation	LiY-11Y 4xAWG 22/19
Wire length	5 m

Electrical data			
Number of electrical connections	2		
Type of electrical connection	M12 (male, 4 pin, straight) / M12 (female, 4 pin, straight)		
Loop resistance per length / maximum	108 mΩ/m		
Insulation resistance coefficient	20 GΩ·m		
Operating voltage			
• maximum	30 V		

Mechanical data	
Number of electrical cores	3
Design of the shield	unshielded
Outer diameter	
• of cable sheath	4.3 mm

Symmetrical tolerance of the outer diameter / of cable sheath	0.15 mm		
Material			
• of the wire insulation	PVC		
• of cable sheath	TPE-U Ether Isolation		
Color			
of the insulation of data wires	brown, white, blue, black		
• of cable sheath	Black		
Bending radius			
• with single bend / minimum permissible	34.4 mm		
• with multiple bends / minimum permissible	64.5 mm		
• with multiple bends / minimum permissible	07.3 Hilli		

Ambient conditions	
Ambient temperature	
during operation	-5 +80 °C
during storage	-40 +80 °C
during transport	-40 +80 °C
during installation	-5 +80 °C
Burning behavior	flame resistant according to AWM STYLE 21317 80°C 30V VW-1 for USA and AWM I/II A/B 80°C 30V FT-1 for Canada

Product features, product functions, product components / general

Prod	LICT	faati	ıro
-100	uca	ıean	ин

• halogen-free

No

Further information / Internet-Links

Internet-Link

• to website: Selector SIMATIC NET

SELECTION TOOL

• to website: Industrial communication

• to website: Industry Mall

• to website: Information and Download Center

• to website: Image database

• to website: CAx Download Manager

• to website: Industry Online Support

https://support.industry.siemens.com/cs/ww/en/view/67384964

http://www.siemens.com/ident/rfid

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

 $\underline{\text{https://support.industry.siemens.com}}$

last modified: 06/23/2020