



Figure similar

LOW-POWER VOLTAGE SENSOR ACCORDING TO IEC 61869-11
 RATIO: 3.25V/-13' @ 20KV/-13' FOR T-CONNECTOR WITH C-CONE
 ACCURACY CLASS: 0.5 (FCM V 3.30 ONWARDS), ELSE 1 INSULATION
 LEVEL: 24/50/125KV VOLTAGE FACTOR: 1,2*UN AND 1,9*UN FOR 8H
 WITH CONNECTION CABLE 2.0 M OPEN END

General technical data	
primary voltage / rated value	20 000 V
secondary voltage / rated value	3.25 V
Product Functions	
is supported / IEC 61869-1	Yes
is supported / IEC 60044-7	No
comparison of primary values required	No
Supply voltage	
withstand voltage / at DC / limited to 15 min	72 kV
medium voltage / minimum rated value	10 kV
line frequency	50 ... 60 Hz
Mechanical Design	
weight	700 g
dimensions / acc. to EN 50181, type C	Yes
length / of connection cable	2 m
projection / of T-plug incl. screw	45 mm
Environmental conditions	
ambient temperature / during operation	-40 ... +80 °C
ambient temperature / during storage	-40 ... +80 °C
Further information	

Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=6MD2320-0AA07-1AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/6MD2320-0AA07-1AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=6MD2320-0AA07-1AA0

Tender specifications

<http://www.siemens.com/specifications>

