

THE DI-2113 MODULE WITH A MICROPROCESSOR ONBOARD PROVIDES 64 BINARY INPUTS (8X8) WITH SCANNING AND CHANGE MONITORING TO THE 1MS SCALE. INPUT VOLTAGE: 48-60VDC

General technical data	
consumed active power / rated value / maximum	1 000 mW
surge voltage / rated value	2 kV
surge voltage resistance	5 kV
Measuring functions	
sampling interval	1 ms
Supply voltage	
supply voltage / at DC / rated value	4.75 ... 5.25 V
type of voltage / of the supply voltage	DC
Inputs / Outputs	
number of isolated input groups	8
number of digital inputs	64
input voltage / at DC / per input	48 ... 60 V
input voltage / per input	36 ... 78 V
consumed current / per input	0.5 ... 2.5 mA
product feature / galvanic isolation of the inputs	Yes
Mechanical Design	
width	20.2 mm
height	233.4 mm
depth	160 mm
fastening method / standard rail mounting	No
fastening method / wall mounting	No
fastening method / rack mounting	Yes
connectable conductor cross-section	0.5 mm ²
product feature / plug-in terminal blocks	No
product function / with function display	Yes
product function / status display	Yes
Degree of protection / protection class	
operating resource protection class	II
degree of pollution	2
protection class IP / on the front	IP20
Environmental conditions	
ambient temperature / during operation	-5 ... +55 °C
ambient temperature / during storage	-30 ... +85 °C
relative humidity	5 ... 95 %
mounting height in relation to mean sea level / maximum	3 000 m
air pressure / maximum	106 kPa
Approval certification	
certificate of suitability / CE marking	Yes
certificate of suitability / UL approval	No
Further information	

Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=6MF1013-0CB13-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/6MF1013-0CB13-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=6MF1013-0CB13-0AA0

Tender specifications

