

SICAM AK 3 RACK (44U WIDTH, 8U HEIGHT) WITH ROOM FOR 9 DOUBLE-EUROFORMAT MODULES, THEREOF * 1 MASTER CONTROL ELEMENT CP-2016 AND * UP TO 8 PROCESSING, COMMUNICATION, AND PERIPHERAL ELEMENTS * UP TO 2 POWER SUPPLIES PS-262X (IN CASE OF REDUNDANT POWER SUPPLY ONLY 8 DOUBLE-EUROFORMAT MODULES POSSIBLE) CONNECTORS: * 9X AX PERIPHERAL BUS * 1X FOR REDUNDANCY SWITCH EMIC * 2X REDUNDANCY LINK THE RACK CAN BE USED FOR REAR PANEL INSTALLATION (WALL- MOUNTINGKIT AND A COVER FOR THE INTERFACES).

Supply voltage	
supply voltage	5.1 V
Mechanical Design	
width	295 mm
height	320 mm
depth	280 mm
number of slots / for modules	9
fastening method / standard rail mounting	No
fastening method / wall mounting	Yes
fastening method / rack mounting	Yes
material / of the enclosure	metal
Degree of protection / protection class	
operating resource protection class	II
degree of pollution	2
protection class IP / on the front	IP20
Environmental conditions	
ambient temperature / during operation	-5 ... +55 °C
ambient temperature / during storage	-30 ... +85 °C
relative humidity	5 ... 95 %
mounting height in relation to mean sea level / maximum	3 000 m
air pressure / maximum	106 kPa
Approval certification	
certificate of suitability / CE marking	Yes
certificate of suitability / UL approval	No
Further information	

Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=6MF1113-0CJ44-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/6MF1113-0CJ44-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=6MF1113-0CJ44-0AA0

Tender specifications

<http://www.siemens.com/specifications>

