

Product type designation

SINAUT ST1/ST7, LTOP1

SINAUT ST7, LTOP1 SINGLE LINE TRANSFORMER WITH 1
OVERVOLTAGE PROTECTION MODULE OPM, FOR
APPLICATION AT THE START OR AT THE END OF A 2-WIRE
CABLE



Electrical data

Transmission frequency	300 Hz ... 35 kHz
------------------------	-------------------

Permitted ambient conditions

Ambient temperature

• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C

Installation location	As near as possible to where the cable enters the building
-----------------------	--

Protection class IP	IP20
---------------------	------

Design, dimensions and weight

Width	90 mm
Height	75 mm
Depth	110 mm
Net weight	300 g
Mounting type	DIN rail TS35 (35 mm, EN 50 022)

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

last modified:

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://www.siemens.com/industrymall>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

08/11/2016