



Figure similar

Data sheet for SINAMICS DCM

Article No. : 6RA8081-6DS22-0AA0-Z
L04+L10

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data	
Armature	
Rated supply voltage armature	400 V
Rated DC voltage	485 V
Rated input current armature	332 A
Rated DC current	400 A
Field	
Field power unit	Without field power unit
Rated supply voltage field	2AC 400V
Rated DC current	25 A
Converter	
Mode of operation	Two-quadrant operation
Rated power	194 kW
Power loss	1,375 W
Degree of protection	IP00
Installation altitude	1,000 m
Dimensions (H x W x D)	625 x 268 x 275 mm
Weight approx.	28 kg

Search values	
Type of construction	Chassis unit
Rated voltage armature	420 V
Rated armature current	400 A
Rated excitation voltage	320 V
Rated excitation current	25 A
Max. overvoltage of AC supply	0 %
Installation altitude	1,000 m
Coolant temperature	40 °C
Mode of operation	Two-quadrant operation
Load class	Class DC I (continuous duty)

Accessories	
3NE3233	Fuse armature AC
OHNE	?OZ_KOMP_1_6RA80 OHNE?
OHNE	?OZ_KOMP_2_6RA80 OHNE?
OHNE	?OZ_KOMP_3_6RA80 OHNE?

Special design	
L04	Armature supply with low voltage 15 up to 50 V
L10	Without field power stack