

MICROMASTER 4 AC COMMUTATION CHOKE 200V-240V 1AC
8,1A FOOTPRINT FSA - 3.6MH NOT FOOTPRINT FOR V20



Figure similar

Order number	
Phase number / of the input voltage	1
Type of voltage / of the input voltage	AC
Input voltage	200 ... 240
Output current / rated value	8.1 A
Power loss [W]	
• at 50 Hz	Wert fehlt!
• at 60 Hz	Wert fehlt!
Type of electrical connection	
• for mains supply line	screw-type terminal
• for load-side outgoing feeder	Pigtail
Type of connectable conductor cross-section / for load-side outgoing feeder	Wert fehlt!
Connectable conductor cross-section	
• for mains supply line	Wert fehlt!
Wire length / of connecting cable / for load-side outgoing feeder	0.39 m
Type of electrical connection / for PE conductor	M5 stud

Protection class IP	IP20
Width	75.5 mm
Height	200 mm
Depth	50 mm
Net weight	1.32 kg
Certificate of suitability	cURus

Further information

Information und Download Center

https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx

Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/6SE6400-3CC01-0AB3/all>

Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SE6400-3CC01-0AB3/all>