

MICROMASTER 4 AC COMMUTATION CHOKE 200V-240V 3AC  
15,7A FOOTPRINT FSC - 0.57MH



Figure similar

Order number	
Phase number / of the input voltage	3
Type of voltage / of the input voltage	AC
Input voltage	200 ... 240
Output current / rated value	15.7 A
Power loss [W]	
• at 50 Hz	Wert fehlt!
• at 60 Hz	Wert fehlt!
Type of electrical connection	
• for mains supply line	screw-type terminal
• for load-side outgoing feeder	Pigtail
Type of connectable conductor cross-section / for load-side outgoing feeder	Wert fehlt!
Connectable conductor cross-section	
• for mains supply line	Wert fehlt!
Wire length / of connecting cable / for load-side outgoing feeder	0.49 m
Type of electrical connection / for PE conductor	M5 stud

Protection class IP	IP20
Width	185 mm
Height	245 mm
Depth	50 mm
Net weight	4.08 kg
Certificate of suitability	cURus

#### Further information

##### Information und Download Center

[https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order\\_form.aspx](https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx)

##### Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

##### Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Catagog/Product/6SE6400-3CC01-7CC3/all>

##### Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SE6400-3CC01-7CC3/all>