

MICROMASTER 4 BRAKING RESISTOR 200-240 V 3,3R 50000 W
PK 2500 W CONT 650 X 395 X 315 MM H X W X D IP20



Figure similar

Order number	
Phase number / of the input voltage	Wert fehlt!
Type of voltage / of the input voltage	Wert fehlt!
Input voltage	Wert fehlt! ... Wert fehlt!
DC link voltage	450
Consumed active power / rated value	2.5 kW
• maximum	50 kW
Type of electrical connection / for power cable	M6 screw studs
Connectable conductor cross-section / for power cable	35 mm ²
Design of the temperature switch	Normally closed contact
Input voltage / of the temperature switch / at AC / maximum	Wert fehlt!
Input current / of the temperature switch / at AC / maximum	2.5 A
Connectable conductor cross-section / on the temperature switch / maximum	2.5 mm ²
Type of electrical connection / of the protective conductor connection	M6 screw studs

Design of the protective conductor connection / on enclosure	M6 screw studs
Protection class IP	IP20
Electrical resistance / of the braking resistor	3.3 Ω
Width	395 mm
Height	650 mm
Depth	315 mm
Net weight	16.7 kg

Further information

Information und Download Center

https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx

Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/6SE6400-4BC22-5FA0/all>

Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SE6400-4BC22-5FA0/all>