

MICROMASTER 4 BRAKING RESISTOR 380-480 V 15R 44000 W  
PK 2200 W CONT 301 X 326 X 484 MM H X W X D IP20



Figure similar

|                                                                           |                             |
|---------------------------------------------------------------------------|-----------------------------|
| Order number                                                              |                             |
| Phase number / of the input voltage                                       | Wert fehlt!                 |
| Type of voltage / of the input voltage                                    | Wert fehlt!                 |
| Input voltage                                                             | Wert fehlt! ... Wert fehlt! |
| DC link voltage                                                           | 900                         |
| Consumed active power / rated value                                       | 2.2 kW                      |
| • maximum                                                                 | 44 kW                       |
| Type of electrical connection / for power cable                           | M6 screw studs              |
| Connectable conductor cross-section / for power cable                     | 16 mm²                      |
| Design of the temperature switch                                          | Normally closed contact     |
| Input voltage / of the temperature switch / at AC / maximum               | Wert fehlt!                 |
| Input current / of the temperature switch / at AC / maximum               | 2.5 A                       |
| Connectable conductor cross-section / on the temperature switch / maximum | 2.5 mm²                     |
| Type of electrical connection / of the protective conductor connection    | M6 screw studs              |

|                                                              |                |
|--------------------------------------------------------------|----------------|
| Design of the protective conductor connection / on enclosure | M6 screw studs |
| Protection class IP                                          | IP20           |
| Electrical resistance / of the braking resistor              | 15 $\Omega$    |
| Width                                                        | 326 mm         |
| Height                                                       | 301 mm         |
| Depth                                                        | 484 mm         |
| Net weight                                                   | 11 kg          |

#### Further information

##### Information und Download Center

[https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order\\_form.aspx](https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx)

##### Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

##### Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/6SE6400-4BD22-2EA1/all>

##### Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SE6400-4BD22-2EA1/all>