

SINAMICS LINE REACTOR FOR 36 KW SMART LINE MODULE
INPUT: 3-PH 380-480 V, 50/60 HZ



Figure similar

Order number	
Phase number / of the input voltage	3
Type of voltage / of the input voltage	AC
Input voltage	380 ... 480
Output current / rated value	69 A
Power loss [W]	
• at 50 Hz	Wert fehlt!
• at 60 Hz	Wert fehlt!
Type of electrical connection	
• for mains supply line	screw-type terminal
• for load-side outgoing feeder	screw terminals
Type of connectable conductor cross-section / for load-side outgoing feeder	Wert fehlt!
Connectable conductor cross-section	
• for mains supply line	Wert fehlt!
• for load-side outgoing feeder	16 mm²
Type of electrical connection / for PE conductor	M6 screw studs
Protection class IP	IP20

Width	228 mm
Height	235 mm
Depth	224 mm
Net weight	17 kg
Certificate of suitability	cURus

Further information

Information und Download Center

https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx

Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/6SL3000-0CE23-6AA0/all>

Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SL3000-0CE23-6AA0/all>