

SINAMICS LINE REACTOR FOR 100KW BASIC LINE MODULE
INPUT: 3-PH 380-480V, 50/60HZ



Figure similar

Order number	
Phase number / of the input voltage	3
Type of voltage / of the input voltage	AC
Input voltage	380 ... 480
Output current / rated value	185 A
Power loss [W]	
• at 50 Hz	Wert fehlt!
• at 60 Hz	Wert fehlt!
Type of electrical connection	
• for mains supply line	Flat connector for M8 screw
• for load-side outgoing feeder	flat connector for M8 screw
Type of connectable conductor cross-section / for load-side outgoing feeder	Wert fehlt!
Connectable conductor cross-section	
• for mains supply line	Wert fehlt!
Protection class IP	IP00
Width	261 mm
Height	262 mm

Depth	214 mm
Net weight	21.7 kg
Certificate of suitability	cURus

Further information

Information und Download Center

https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx

Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/6SL3000-0CE31-0AA0/all>

Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SL3000-0CE31-0AA0/all>