

SINAMICS LINE REACTOR INPUT: 3-PH. 660-690 V, 50/60 HZ, 270 A



Figure similar

Order number	
Phase number / of the input voltage	3
Type of voltage / of the input voltage	AC
Input voltage	500 ... 690
Output current / rated value	270 A
Power loss [W]	
• at 50 Hz	Wert fehlt!
• at 60 Hz	Wert fehlt!
Type of electrical connection	
• for mains supply line	1 x hole for M10
Type of connectable conductor cross-section / for load-side outgoing feeder	Wert fehlt!
Connectable conductor cross-section	
• for mains supply line	Wert fehlt!
Protection class IP	IP00
Width	270 mm
Height	230 mm
Depth	201.5 mm

Net weight	27.9 kg
Certificate of suitability	cURus

Further information

Information und Download Center

https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx

Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/6SL3000-0CH32-7AA0/all>

Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SL3000-0CH32-7AA0/all>