

SIMODRIVE 611 LINE REACTOR FOR 120 KW INFEED /
 REGENERATIV FEEDBACK MODULE INPUT: 3AC 380-480V,
 50/60HZ"



Figure similar

Order number	
Phase number / of the input voltage	3
Type of voltage / of the input voltage	AC
Input voltage	380 ... 480
Output current / rated value	225 A
Power loss [W]	
• at 50 Hz	Wert fehlt!
• at 60 Hz	Wert fehlt!
Type of electrical connection	
• for mains supply line	M10 connecting lug
• for load-side outgoing feeder	M10 connecting lug
Type of connectable conductor cross-section / for load-side outgoing feeder	Wert fehlt!
Connectable conductor cross-section	
• for mains supply line	Wert fehlt!
Type of electrical connection / for PE conductor	M10 connecting lug
Protection class IP	IP00
Width	225 mm

Height	490 mm
Depth	250 mm
Net weight	64 kg
Certificate of suitability	cURus

Further information

Information und Download Center

https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx

Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Catag/Product/6SL3000-0DE31-2BA0/all>

Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SL3000-0DE31-2BA0/all>