



Figure similar

Data sheet for Control Supply Module

Article No. : 6SL3100-1DE22-0AA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data	
DC link	
Voltage ¹⁾	510 ... 720 V
Output	
Voltage	24.0 ... 28.8 V
Rated data	
Input	
Rated current (3 AC 400 V), max.	2 A
Rated current (600 V DC)	1.1 A
Output	
Rated current	20 A
Current carrying capacity	
24 V busbars	20 A
DC link busbars	100 A

¹⁾Operation in 300 ... 430 V DC range permitted briefly for < 1 min
²⁾Depth, with spacer (included in scope of supply)

Mechanical data	
Dimensions	
Width	50 mm (1.97 in)
Height	380 mm (14.96 in)
Depth ²⁾	270 mm (10.63 in)
Net weight	4.8 kg (10.58 lb)
Type of construction	Booksize
General technical specifications	
RI suppression	Category C2 in accordance with EN 61800-3
Ambient conditions	
Type of cooling	Internal air cooling
Connections	
Line side	
Design	screw-type terminal
Conductor cross-section	0.2 ... 4.0 mm² (AWG 24 ... AWG 12)
PE conductor	
Design	M5 screw
Standards	
Compliance with standards	cULus