



Figure similar

### MLFB-Ordering data

6SL3121-1TE26-0AA3

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		Ambient conditions	
DC link voltage	DC 510 ... 720 V	Installation altitude (without derating)	1000 m (3281 ft)
Electronics power supply	DC 24 V -15 % / +20 %	Cooling <sup>8)</sup>	External air cooling
Current demand, max.	1.20 A	Cooling air requirement	0.031 m <sup>3</sup> /s
DC-link current I <sub>d</sub>	72.0 A	<b>Ambient temperature</b>	
<b>Output current</b>		During operation	
Rated value I <sub>N</sub>	60.0 A	0 ... 40 °C (32 ... 104 °F)	
Base load current I <sub>H</sub>	52.0 A	<b>Connections</b>	
For S6 duty (40%) I <sub>S6</sub>	80.0 A	<b>Motor end</b>	
I <sub>max</sub>	113.0 A	Version	M6 bolt (X1)
<b>Type rating <sup>2)</sup></b>		Conductor cross-section	3 ... 50 mm <sup>2</sup> (14 ... 1 AWG)
Based on I <sub>N</sub>	32.0 kW	PE connection	M6 screw
Based on I <sub>H</sub>	28.0 kW	<b>Max. motor cable length</b>	
Rated pulse frequency	4.00 kHz	Shielded	100 m (328 ft)
<b>Current carrying capacity</b>		Unshielded	150 m (492 ft)
DC link busbars	200 A	<b>Standards</b>	
24 V busbars	20 A	Compliance with standards	CE, cULus
DC link capacitance	1410 μF	Safety Integrated	SIL 2 acc. to IEC 61508, PL d acc. to EN ISO 13849-1, Category 3 acc. to EN ISO 13849-1

MLFB-Ordering data

6SL3121-1TE26-0AA3



Figure similar

### Mechanical data

#### Line side

Width	150.00 mm (5.91 in)
Height	380.00 mm (14.96 in)
Depth	226.00 mm (8.90 in)
Degree of protection	IP20 / UL open type
Type of construction	Booksize
Net weight	13.4 kg (29.54 lb)

### General tech. specifications

Sound pressure level (1m)	65.0 dB
Power loss, max. <sup>9)</sup>	0.46 kW

2) Rated output of a typical standard asynchronous motor at 400 V 3 AC

8) Power units with intensified air cooling thanks to integrated fan

9) Power loss of the Motor Module with rated power including losses of the 24 V DC electronics power supply