

## Data sheet for Line filter

Article No. : 6SL3203-0BE21-2VA0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :



Figure similar

| Rated data |  |
|------------|--|
|------------|--|

Input

|                  |               |
|------------------|---------------|
| Number of phases | 3 AC          |
| Line voltage     | 200 ... 480 V |

Output

|               |        |
|---------------|--------|
| Rated current | 12.0 A |
|---------------|--------|

| Mechanical data |  |
|-----------------|--|
|-----------------|--|

|                      |                     |
|----------------------|---------------------|
| Degree of protection | IP20 / UL open type |
| Net weight           | 1.92 kg (4.23 lb)   |

Dimensions

|        |                    |
|--------|--------------------|
| Width  | 75.0 mm (2.95 in)  |
| Height | 170.0 mm (6.69 in) |
| Depth  | 140.0 mm (5.51 in) |

| Connections |  |
|-------------|--|
|-------------|--|

Line side

|                         |                     |
|-------------------------|---------------------|
| Version                 | screw-type terminal |
| Conductor cross-section | 0.25 ... 10.00 mm²  |

Load side

|              |                      |
|--------------|----------------------|
| Version      | Screw-type terminals |
| Cable length | 20.00 m              |

PE connection

|         |                                |
|---------|--------------------------------|
| Version | On housing with M6 screw studs |
|---------|--------------------------------|