

MLFB-Ordering data

6SL3210-1NE23-8AL1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
Input		Power factor λ0.90	
Number of phases	3 AC	Offset factor cos φ0.95	
Line voltage	380 ... 480 V ±10 %	Efficiency η0.98	
Line frequency	47 ... 63 Hz	Sound pressure level (1m)65 dB	
Rated current (LO)	39.20 A	Power loss0.45 kW	
Rated current (HO)	33.00 A	Filter class (integrated)Class A	
Output		Ambient conditions	
Number of phases	3 AC	CoolingInternal air cooling	
Rated voltage	400 V	Cooling air requirement0.019 m³/s (0.671 ft³/s)	
Rated current (LO)	38.00 A	Installation altitude1000 m (3280.84 ft)	
Rated current (HO)	32.00 A	Ambient temperature	
Max. output current	64.00 A	Operation LO-10 ... 40 °C (14 ... 104 °F)	
Rated power IEC 400V (LO)	18.50 kW	Operation HO-10 ... 50 °C (14 ... 122 °F)	
Rated power NEC 480V (LO)	25.00 hp	Transport-40 ... 70 °C (-40 ... 158 °F)	
Rated power IEC 400V (HO)	15.00 kW	Storage-40 ... 70 °C (-40 ... 158 °F)	
Rated power NEC 480V (HO)	20.00 hp	Relative humidity	
Pulse frequency	4 kHz		
Output frequency for vector control	0 ... 200 Hz	Max. operation95 % RH, condensation not permitted	
Output frequency for V/f control	0 ... 550 Hz		

Overload capability

Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

SIEMENS

Data sheet for SINAMICS Power Module PM230

No image available for this configuration.

MLFB-Ordering data


6SL3210-1NE23-8AL1

Figure similar

Mechanical data	Connections
Degree of protection	IP20 / UL open type
Size	FSC
Net weight	5.10 kg (11.24 lb)
Width	140 mm (5.51 in)
Height	355 mm (13.98 in)
Depth	165 mm (6.50 in)
Line side	
Version	Plug-in screw terminals
Conductor cross-section	6.00 ... 16.00 mm² (AWG 10 ... AWG 6)
Motor end	
Version	Plug-in screw terminals
Conductor cross-section	6.00 ... 16.00 mm² (AWG 10 ... AWG 6)

Converter losses to EN 50598-2*

Efficiency class	IE2
Comparison with the reference converter (90% / 100%)	-67.72 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter without options/components.

*converted values

Max. motor cable length	
Shielded	25 m (82.02 ft)
Unshielded	100 m (328.08 ft)

Standards

Compliance with standards	UL, CE, C-Tick (RCM), KCC
CE marking	Low-voltage directive 2006/95/EC