

MLFB-Ordering data

6SL3210-5BB17-5AV0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data	General tech. specifications																
Input <table> <tr> <td>Number of phases</td><td>1 AC</td></tr> <tr> <td>Line voltage</td><td>200 ... 240 V -10 % +10 %</td></tr> <tr> <td>Line frequency</td><td>47 ... 63 Hz</td></tr> </table>	Number of phases	1 AC	Line voltage	200 ... 240 V -10 % +10 %	Line frequency	47 ... 63 Hz	<table> <tr> <td>Power factor λ</td><td>0.72</td></tr> <tr> <td>Offset factor $\cos \varphi$</td><td>0.95</td></tr> <tr> <td>Efficiency η</td><td>0.98</td></tr> <tr> <td>Filter class (integrated)</td><td>Class A</td></tr> </table>	Power factor λ	0.72	Offset factor $\cos \varphi$	0.95	Efficiency η	0.98	Filter class (integrated)	Class A		
Number of phases	1 AC																
Line voltage	200 ... 240 V -10 % +10 %																
Line frequency	47 ... 63 Hz																
Power factor λ	0.72																
Offset factor $\cos \varphi$	0.95																
Efficiency η	0.98																
Filter class (integrated)	Class A																
Output <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Rated voltage</td><td>230 V</td></tr> <tr> <td>Rated power (HO)</td><td>0.75 kW / 0.75 hp</td></tr> <tr> <td>Rated power (LO)</td><td>0.75 kW / 0.75 hp</td></tr> <tr> <td>Rated current (HO)</td><td>3.90 A</td></tr> <tr> <td>Rated current (LO)</td><td>3.90 A</td></tr> </table>	Number of phases	3 AC	Rated voltage	230 V	Rated power (HO)	0.75 kW / 0.75 hp	Rated power (LO)	0.75 kW / 0.75 hp	Rated current (HO)	3.90 A	Rated current (LO)	3.90 A	Ambient conditions <table> <tr> <td>Cooling</td><td>convection cooling</td></tr> <tr> <td>Installation altitude</td><td>1000 m (3281 ft)</td></tr> </table>	Cooling	convection cooling	Installation altitude	1000 m (3281 ft)
Number of phases	3 AC																
Rated voltage	230 V																
Rated power (HO)	0.75 kW / 0.75 hp																
Rated power (LO)	0.75 kW / 0.75 hp																
Rated current (HO)	3.90 A																
Rated current (LO)	3.90 A																
Cooling	convection cooling																
Installation altitude	1000 m (3281 ft)																
<table> <tr> <td>Pulse frequency</td><td>8.00 kHz</td></tr> <tr> <td>Output frequency</td><td>0 ... 550 Hz</td></tr> </table>	Pulse frequency	8.00 kHz	Output frequency	0 ... 550 Hz	Ambient temperature <table> <tr> <td>Operation</td><td>-10 ... 60 °C (14 ... 140 °F)</td></tr> <tr> <td>Storage</td><td>-40 ... 70 °C (-40 ... 158 °F)</td></tr> </table>	Operation	-10 ... 60 °C (14 ... 140 °F)	Storage	-40 ... 70 °C (-40 ... 158 °F)								
Pulse frequency	8.00 kHz																
Output frequency	0 ... 550 Hz																
Operation	-10 ... 60 °C (14 ... 140 °F)																
Storage	-40 ... 70 °C (-40 ... 158 °F)																
	Relative humidity <table> <tr> <td>Max. operation</td><td>95 %</td></tr> </table>	Max. operation	95 %														
Max. operation	95 %																
	Communication <table> <tr> <td>Communication</td><td>USS, Modbus RTU</td></tr> </table>	Communication	USS, Modbus RTU														
Communication	USS, Modbus RTU																
	Standards <table> <tr> <td>Compliance with standards</td><td>CE, cULus, C-Tick (RCM), KC</td></tr> <tr> <td>CE marking</td><td>EN 61800-5-1 /EN 60204-1 and EN 61800-3</td></tr> </table>	Compliance with standards	CE, cULus, C-Tick (RCM), KC	CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3												
Compliance with standards	CE, cULus, C-Tick (RCM), KC																
CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																

Overload capability

Low Overload (LO)

110 % rated output current for 60 s, cycle time 300 s

High Overload (HO)

150 % rated output current for 60 s, cycle time 300 s

SIEMENS

Data sheet for SINAMICS V20

MLFB-Ordering data 6SL3210-5BB17-5AV0



Figure similar

Mechanical data	Connections
-----------------	-------------

Mounting position	Wall mounting / side-by-side mounting
Degree of protection	IP20 / UL open type
Size	FSA
Net weight	1.10 kg (2.43 lb)
Width	90.0 mm (3.54 in)
Height	150.0 mm (5.91 in)
Depth	145.5 mm (5.73 in)

Max. motor cable length	
Shielded	10 m (33 ft)
Unshielded	50 m (164 ft)

Inputs / outputs

Standard digital inputs	
Number	4

Digital outputs	
Number as relay changeover contact	1
Number as transistor	1

Analog inputs	
Number	2 (Can be used as additional digital input)

Analog outputs	
Number	1