

MLFB-Ordering data

6SL3210-5BE15-5UV0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data	General tech. specifications																														
Input <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Line voltage</td><td>380 ... 480 V -15 % +10 %</td></tr> <tr> <td>Line frequency</td><td>47 ... 63 Hz</td></tr> </table>	Number of phases	3 AC	Line voltage	380 ... 480 V -15 % +10 %	Line frequency	47 ... 63 Hz	<table> <tr> <td>Power factor λ</td><td>0.72</td></tr> <tr> <td>Offset factor $\cos \varphi$</td><td>0.95</td></tr> <tr> <td>Efficiency η</td><td>0.98</td></tr> <tr> <td>Filter class (integrated)</td><td>Unfiltered</td></tr> </table>	Power factor λ	0.72	Offset factor $\cos \varphi$	0.95	Efficiency η	0.98	Filter class (integrated)	Unfiltered																
Number of phases	3 AC																														
Line voltage	380 ... 480 V -15 % +10 %																														
Line frequency	47 ... 63 Hz																														
Power factor λ	0.72																														
Offset factor $\cos \varphi$	0.95																														
Efficiency η	0.98																														
Filter class (integrated)	Unfiltered																														
Output <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Rated voltage</td><td>400 V</td></tr> <tr> <td>Rated power (HO)</td><td>0.55 kW / 0.75 hp</td></tr> <tr> <td>Rated power (LO)</td><td>0.55 kW / 0.75 hp</td></tr> <tr> <td>Rated current (HO)</td><td>1.70 A</td></tr> <tr> <td>Rated current (LO)</td><td>1.70 A</td></tr> <tr> <td>Rated current (HO) at 480V</td><td>1.70 A</td></tr> <tr> <td>Rated current (LO) at 480V</td><td>1.70 A</td></tr> <tr> <td>Pulse frequency</td><td>4.00 kHz</td></tr> <tr> <td>Output frequency</td><td>0 ... 550 Hz</td></tr> </table>	Number of phases	3 AC	Rated voltage	400 V	Rated power (HO)	0.55 kW / 0.75 hp	Rated power (LO)	0.55 kW / 0.75 hp	Rated current (HO)	1.70 A	Rated current (LO)	1.70 A	Rated current (HO) at 480V	1.70 A	Rated current (LO) at 480V	1.70 A	Pulse frequency	4.00 kHz	Output frequency	0 ... 550 Hz	Ambient conditions <table> <tr> <td>Cooling</td><td>convection cooling</td></tr> <tr> <td>Installation altitude</td><td>1000 m (3281 ft)</td></tr> </table> Ambient temperature <table> <tr> <td>Operation</td><td>-10 ... 60 °C (14 ... 140 °F)</td></tr> <tr> <td>Storage</td><td>-40 ... 70 °C (-40 ... 158 °F)</td></tr> </table> Relative humidity <table> <tr> <td>Max. operation</td><td>95 %</td></tr> </table>	Cooling	convection cooling	Installation altitude	1000 m (3281 ft)	Operation	-10 ... 60 °C (14 ... 140 °F)	Storage	-40 ... 70 °C (-40 ... 158 °F)	Max. operation	95 %
Number of phases	3 AC																														
Rated voltage	400 V																														
Rated power (HO)	0.55 kW / 0.75 hp																														
Rated power (LO)	0.55 kW / 0.75 hp																														
Rated current (HO)	1.70 A																														
Rated current (LO)	1.70 A																														
Rated current (HO) at 480V	1.70 A																														
Rated current (LO) at 480V	1.70 A																														
Pulse frequency	4.00 kHz																														
Output frequency	0 ... 550 Hz																														
Cooling	convection cooling																														
Installation altitude	1000 m (3281 ft)																														
Operation	-10 ... 60 °C (14 ... 140 °F)																														
Storage	-40 ... 70 °C (-40 ... 158 °F)																														
Max. operation	95 %																														
	Communication <table> <tr> <td>Communication</td><td>USS, Modbus RTU</td></tr> </table>	Communication	USS, Modbus RTU																												
Communication	USS, Modbus RTU																														
	Standards <table> <tr> <td>Compliance with standards</td><td>CE, cULus, C-Tick (RCM), KC</td></tr> <tr> <td>CE marking</td><td>EN 61800-5-1 /EN 60204-1 and EN 61800-3</td></tr> </table>	Compliance with standards	CE, cULus, C-Tick (RCM), KC	CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																										
Compliance with standards	CE, cULus, C-Tick (RCM), KC																														
CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																														

Overload capability

Low Overload (LO)

110 % rated output current for 60 s, cycle time 300 s

High Overload (HO)

150 % rated output current for 60 s, cycle time 300 s



Figure similar

Mechanical data	Connections																						
<table><tr><td>Mounting position</td><td>Wall mounting / side-by-side mounting</td></tr><tr><td>Degree of protection</td><td>IP20 / UL open type</td></tr><tr><td>Size</td><td>FSA</td></tr><tr><td>Net weight</td><td>0.90 kg (1.98 lb)</td></tr><tr><td>Width</td><td>90.0 mm (3.54 in)</td></tr><tr><td>Height</td><td>150.0 mm (5.91 in)</td></tr><tr><td>Depth</td><td>145.5 mm (5.73 in)</td></tr></table>	Mounting position	Wall mounting / side-by-side mounting	Degree of protection	IP20 / UL open type	Size	FSA	Net weight	0.90 kg (1.98 lb)	Width	90.0 mm (3.54 in)	Height	150.0 mm (5.91 in)	Depth	145.5 mm (5.73 in)	Max. motor cable length <table><tr><td>Shielded</td><td>10 m (33 ft)</td></tr><tr><td>Unshielded</td><td>50 m (164 ft)</td></tr></table> Converter losses to EN 50598-2* <table><tr><td>Efficiency class</td><td>IE2</td></tr><tr><td>Comparison with the reference converter (90% / 100%)</td><td>-22.68 %</td></tr></table> The percentage values show the losses in relation to the rated apparent power of the converter. The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter without options/components. *converted values	Shielded	10 m (33 ft)	Unshielded	50 m (164 ft)	Efficiency class	IE2	Comparison with the reference converter (90% / 100%)	-22.68 %
Mounting position	Wall mounting / side-by-side mounting																						
Degree of protection	IP20 / UL open type																						
Size	FSA																						
Net weight	0.90 kg (1.98 lb)																						
Width	90.0 mm (3.54 in)																						
Height	150.0 mm (5.91 in)																						
Depth	145.5 mm (5.73 in)																						
Shielded	10 m (33 ft)																						
Unshielded	50 m (164 ft)																						
Efficiency class	IE2																						
Comparison with the reference converter (90% / 100%)	-22.68 %																						
Inputs / outputs																							
Standard digital inputs <table><tr><td>Number</td><td>4</td></tr></table> Digital outputs <table><tr><td>Number as relay changeover contact</td><td>1</td></tr><tr><td>Number as transistor</td><td>1</td></tr></table> Analog inputs <table><tr><td>Number</td><td>2 (Can be used as additional digital input)</td></tr></table> Analog outputs <table><tr><td>Number</td><td>1</td></tr></table>	Number	4	Number as relay changeover contact	1	Number as transistor	1	Number	2 (Can be used as additional digital input)	Number	1													
Number	4																						
Number as relay changeover contact	1																						
Number as transistor	1																						
Number	2 (Can be used as additional digital input)																						
Number	1																						