

MLFB-Ordering data

6SL3210-5BE25-5UV0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data	General tech. specifications																																																		
Input <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Line voltage</td><td>380 ... 480 V -15 % +10 %</td></tr> <tr> <td>Line frequency</td><td>47 ... 63 Hz</td></tr> </table> Output <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Rated voltage</td><td>400 V</td></tr> <tr> <td>Rated power (HO)</td><td>5.50 kW / 7.50 hp</td></tr> <tr> <td>Rated power (LO)</td><td>5.50 kW / 7.50 hp</td></tr> <tr> <td>Rated current (HO)</td><td>12.50 A</td></tr> <tr> <td>Rated current (LO)</td><td>12.50 A</td></tr> <tr> <td>Rated current (HO) at 480V</td><td>11.00 A</td></tr> <tr> <td>Rated current (LO) at 480V</td><td>11.00 A</td></tr> <tr> <td>Pulse frequency</td><td>4.00 kHz</td></tr> <tr> <td>Output frequency</td><td>0 ... 550 Hz</td></tr> </table>	Number of phases	3 AC	Line voltage	380 ... 480 V -15 % +10 %	Line frequency	47 ... 63 Hz	Number of phases	3 AC	Rated voltage	400 V	Rated power (HO)	5.50 kW / 7.50 hp	Rated power (LO)	5.50 kW / 7.50 hp	Rated current (HO)	12.50 A	Rated current (LO)	12.50 A	Rated current (HO) at 480V	11.00 A	Rated current (LO) at 480V	11.00 A	Pulse frequency	4.00 kHz	Output frequency	0 ... 550 Hz	<table> <tr> <td>Power factor λ</td><td>0.72</td></tr> <tr> <td>Offset factor $\cos \varphi$</td><td>0.95</td></tr> <tr> <td>Efficiency η</td><td>0.98</td></tr> <tr> <td>Filter class (integrated)</td><td>Unfiltered</td></tr> </table> Ambient conditions <table> <tr> <td>Cooling</td><td>External fan</td></tr> <tr> <td>Installation altitude</td><td>1000 m (3281 ft)</td></tr> </table> Ambient temperature <table> <tr> <td>Operation</td><td>-10 ... 60 °C (14 ... 140 °F)</td></tr> <tr> <td>Storage</td><td>-40 ... 70 °C (-40 ... 158 °F)</td></tr> </table> Relative humidity <table> <tr> <td>Max. operation</td><td>95 %</td></tr> </table> Communication <table> <tr> <td>Communication</td><td>USS, Modbus RTU</td></tr> </table> Standards <table> <tr> <td>Compliance with standards</td><td>CE, cULus, C-Tick (RCM), KC</td></tr> <tr> <td>CE marking</td><td>EN 61800-5-1 /EN 60204-1 and EN 61800-3</td></tr> </table>	Power factor λ	0.72	Offset factor $\cos \varphi$	0.95	Efficiency η	0.98	Filter class (integrated)	Unfiltered	Cooling	External fan	Installation altitude	1000 m (3281 ft)	Operation	-10 ... 60 °C (14 ... 140 °F)	Storage	-40 ... 70 °C (-40 ... 158 °F)	Max. operation	95 %	Communication	USS, Modbus RTU	Compliance with standards	CE, cULus, C-Tick (RCM), KC	CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3
Number of phases	3 AC																																																		
Line voltage	380 ... 480 V -15 % +10 %																																																		
Line frequency	47 ... 63 Hz																																																		
Number of phases	3 AC																																																		
Rated voltage	400 V																																																		
Rated power (HO)	5.50 kW / 7.50 hp																																																		
Rated power (LO)	5.50 kW / 7.50 hp																																																		
Rated current (HO)	12.50 A																																																		
Rated current (LO)	12.50 A																																																		
Rated current (HO) at 480V	11.00 A																																																		
Rated current (LO) at 480V	11.00 A																																																		
Pulse frequency	4.00 kHz																																																		
Output frequency	0 ... 550 Hz																																																		
Power factor λ	0.72																																																		
Offset factor $\cos \varphi$	0.95																																																		
Efficiency η	0.98																																																		
Filter class (integrated)	Unfiltered																																																		
Cooling	External fan																																																		
Installation altitude	1000 m (3281 ft)																																																		
Operation	-10 ... 60 °C (14 ... 140 °F)																																																		
Storage	-40 ... 70 °C (-40 ... 158 °F)																																																		
Max. operation	95 %																																																		
Communication	USS, Modbus RTU																																																		
Compliance with standards	CE, cULus, C-Tick (RCM), KC																																																		
CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																																																		

Overload capability

Low Overload (LO)

110 % rated output current for 60 s, cycle time 300 s

High Overload (HO)

150 % rated output current for 60 s, cycle time 300 s



Figure similar

Mechanical data

Mounting position	Through-hole mounting / wall mounting / side-by-side mounting
Degree of protection	IP20 / UL open type
Size	FSC
Net weight	2.40 kg (5.29 lb)
Width	184.0 mm (7.24 in)
Height	182.0 mm (7.17 in)
Depth	169.0 mm (6.65 in)

Inputs / outputs

Standard digital inputs

Number	4
--------	---

Digital outputs

Number as relay changeover contact	1
Number as transistor	1

Analog inputs

Number	2 (Can be used as additional digital input)
--------	---

Analog outputs

Number	1
--------	---


Connections

Max. motor cable length

Shielded	25 m (82 ft)
Unshielded	50 m (164 ft)

Converter losses to EN 50598-2*

Efficiency class	IE2
Comparison with the reference converter (90% / 100%)	-35.15 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency (f). The values are valid for the basic version of the converter without options/components.

*converted values