



Figure similar

MLFB-Ordering data

6SL3210-5DE12-4UA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		Ambient conditions	
Input		Cooling	
Number of phases	3 AC	natural convection	
Line voltage	380 ... 480 V -15 % +10 %	Installation altitude	
Line frequency	45 ... 66 Hz	1000 m	
Output		Cooling air requirement	
Rated power	0.40 kW	0.005 m³/s (0.177 ft³/s)	
Rated current (IN)	1.20 A	Ambient temperature	
Max. output current	3.60 A	Operation	
Electronic power supply		0 ... 45 °C (32 ... 113 °F)	
Power supply	24 V ±10 %	Storage	
General tech. specifications		-40 ... 70 °C (-40 ... 158 °F)	
Power loss	36.00 W	Transport	
Connections		-40 ... 70 °C (-40 ... 158 °F)	
Motor end		Relative humidity	
Conductor cross-section	1.5 mm²	Max. operation	
Mechanical data		90 %	
Degree of protection	IP20 / UL open type	Standards	
Size	FSA	Compliance with standards	
Net weight	1.85 kg (4.08 lb)	CE	
Width	80.0 mm (3.15 in)		
Height	180.0 mm (7.09 in)		
Depth	200.0 mm (7.87 in)		