



Figure similar

MLFB-Ordering data

6SL3210-5DE13-5UA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data

Input

Number of phases	3 AC
Line voltage	380 ... 480 V -15 % +10 %
Line frequency	45 ... 66 Hz

Output

Rated power	1.00 kW
Rated current (IN)	3.00 A
Max. output current	9.00 A

Electronic power supply

Power supply	24 V ±10 %
--------------	------------

General tech. specifications

Power loss	47.00 W
------------	---------

Connections

Motor end

Conductor cross-section	1.5 mm²
-------------------------	---------

Mechanical data

Degree of protection	IP20 / UL open type
Size	FSA
Net weight	1.85 kg (4.08 lb)
Width	80.0 mm (3.15 in)
Height	180.0 mm (7.09 in)
Depth	200.0 mm (7.87 in)

Ambient conditions

Cooling	natural convection
Installation altitude	1000 m
Cooling air requirement	0.005 m³/s (0.177 ft³/s)

Ambient temperature

Operation	0 ... 45 °C (32 ... 113 °F)
Storage	-40 ... 70 °C (-40 ... 158 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)

Relative humidity

Max. operation	90 %
----------------	------

Standards

Compliance with standards	CE
---------------------------	----