

MLFB-Ordering data

6SL3223-0DE21-5AA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data	General tech. specifications																																												
Input <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Line voltage</td><td>380 ... 480 V ± 10 %</td></tr> <tr> <td>Line frequency</td><td>47 ... 63 Hz</td></tr> <tr> <td>Rated current (LO)</td><td>4.20 A</td></tr> <tr> <td>Rated current (HO)</td><td>3.20 A</td></tr> </table>	Number of phases	3 AC	Line voltage	380 ... 480 V ± 10 %	Line frequency	47 ... 63 Hz	Rated current (LO)	4.20 A	Rated current (HO)	3.20 A	<table> <tr> <td>Power factor λ</td><td>0.90</td></tr> <tr> <td>Offset factor $\cos \varphi$</td><td>0.95</td></tr> <tr> <td>Efficiency η</td><td>0.95</td></tr> <tr> <td>Sound pressure level (1m)</td><td>62 dB</td></tr> <tr> <td>Power loss</td><td>0.08 kW</td></tr> <tr> <td>Filter class (integrated)</td><td>Class A</td></tr> </table>	Power factor λ	0.90	Offset factor $\cos \varphi$	0.95	Efficiency η	0.95	Sound pressure level (1m)	62 dB	Power loss	0.08 kW	Filter class (integrated)	Class A																						
Number of phases	3 AC																																												
Line voltage	380 ... 480 V ± 10 %																																												
Line frequency	47 ... 63 Hz																																												
Rated current (LO)	4.20 A																																												
Rated current (HO)	3.20 A																																												
Power factor λ	0.90																																												
Offset factor $\cos \varphi$	0.95																																												
Efficiency η	0.95																																												
Sound pressure level (1m)	62 dB																																												
Power loss	0.08 kW																																												
Filter class (integrated)	Class A																																												
Output <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Rated voltage</td><td>400 V</td></tr> <tr> <td>Rated current (LO)</td><td>4.10 A</td></tr> <tr> <td>Rated current (HO)</td><td>3.10 A</td></tr> <tr> <td>Max. output current</td><td>6.20 A</td></tr> <tr> <td>Rated power IEC 400V (LO)</td><td>1.50 kW</td></tr> <tr> <td>Rated power NEC 480V (LO)</td><td>2.00 hp</td></tr> <tr> <td>Rated power IEC 400V (HO)</td><td>1.10 kW</td></tr> <tr> <td>Rated power NEC 480V (HO)</td><td>1.50 hp</td></tr> <tr> <td>Pulse frequency</td><td>4 kHz</td></tr> <tr> <td>Output frequency for vector control</td><td>0 ... 200 Hz</td></tr> <tr> <td>Output frequency for V/f control</td><td>0 ... 550 Hz</td></tr> </table>	Number of phases	3 AC	Rated voltage	400 V	Rated current (LO)	4.10 A	Rated current (HO)	3.10 A	Max. output current	6.20 A	Rated power IEC 400V (LO)	1.50 kW	Rated power NEC 480V (LO)	2.00 hp	Rated power IEC 400V (HO)	1.10 kW	Rated power NEC 480V (HO)	1.50 hp	Pulse frequency	4 kHz	Output frequency for vector control	0 ... 200 Hz	Output frequency for V/f control	0 ... 550 Hz	Ambient conditions <table> <tr> <td>Cooling</td><td>Internal air cooling</td></tr> <tr> <td>Cooling air requirement</td><td>0.007 m³/s (0.247 ft³/s)</td></tr> <tr> <td>Installation altitude</td><td>1000 m (3280.84 ft)</td></tr> <tr> <td>Ambient temperature</td><td></td></tr> <tr> <td>Operation LO</td><td>0 ... 40 °C (32 ... 104 °F)</td></tr> <tr> <td>Operation HO</td><td>0 ... 50 °C (32 ... 122 °F)</td></tr> <tr> <td>Transport</td><td>-25 ... 55 °C (-13 ... 131 °F)</td></tr> <tr> <td>Storage</td><td>-25 ... 55 °C (-13 ... 131 °F)</td></tr> <tr> <td>Relative humidity</td><td></td></tr> <tr> <td>Max. operation</td><td>95 % RH, condensation not permitted</td></tr> </table>	Cooling	Internal air cooling	Cooling air requirement	0.007 m ³ /s (0.247 ft ³ /s)	Installation altitude	1000 m (3280.84 ft)	Ambient temperature		Operation LO	0 ... 40 °C (32 ... 104 °F)	Operation HO	0 ... 50 °C (32 ... 122 °F)	Transport	-25 ... 55 °C (-13 ... 131 °F)	Storage	-25 ... 55 °C (-13 ... 131 °F)	Relative humidity		Max. operation	95 % RH, condensation not permitted
Number of phases	3 AC																																												
Rated voltage	400 V																																												
Rated current (LO)	4.10 A																																												
Rated current (HO)	3.10 A																																												
Max. output current	6.20 A																																												
Rated power IEC 400V (LO)	1.50 kW																																												
Rated power NEC 480V (LO)	2.00 hp																																												
Rated power IEC 400V (HO)	1.10 kW																																												
Rated power NEC 480V (HO)	1.50 hp																																												
Pulse frequency	4 kHz																																												
Output frequency for vector control	0 ... 200 Hz																																												
Output frequency for V/f control	0 ... 550 Hz																																												
Cooling	Internal air cooling																																												
Cooling air requirement	0.007 m ³ /s (0.247 ft ³ /s)																																												
Installation altitude	1000 m (3280.84 ft)																																												
Ambient temperature																																													
Operation LO	0 ... 40 °C (32 ... 104 °F)																																												
Operation HO	0 ... 50 °C (32 ... 122 °F)																																												
Transport	-25 ... 55 °C (-13 ... 131 °F)																																												
Storage	-25 ... 55 °C (-13 ... 131 °F)																																												
Relative humidity																																													
Max. operation	95 % RH, condensation not permitted																																												

Overload capability

Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

SIEMENS

Data sheet for SINAMICS Power Module PM230

No image
available for this
configuration.


MLFB-Ordering data

6SL3223-0DE21-5AA0

Figure similar

Mechanical data	Connections
Degree of protection	IP55 / UL type 12
Size	FSA
Net weight	4.30 kg (9.48 lb)
Width	154 mm (6.06 in)
Height	460 mm (18.11 in)
Depth	249 mm (9.80 in)
Line side	
Version	Plug-in screw terminals
Conductor cross-section	1.00 ... 2.50 mm² (AWG 18 ... AWG 14)
Motor end	
Version	Plug-in screw terminals
Conductor cross-section	1.00 ... 2.50 mm² (AWG 18 ... AWG 14)

Converter losses to EN 50598-2*	
Efficiency class	IE2
Comparison with the reference converter (90% / 100%)	-74.97 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter without options/components.

*converted values

Max. motor cable length	
Shielded	25 m (82.02 ft)
Unshielded	100 m (328.08 ft)

Standards	
Compliance with standards	UL, CE, C-Tick (RCM)
CE marking	Low-voltage directive 2006/95/EC