



Figure similar

MLFB-Ordering data

6SL3223-0DE22-2AG1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
Input		Power factor λ	0.90
Number of phases	3 AC	Offset factor $\cos \varphi$	0.95
Line voltage	380 ... 480 V ± 10 %	Efficiency η	0.96
Line frequency	47 ... 63 Hz	Sound pressure level (1m)	62 dB
Rated current (LO)	6.10 A	Power loss	0.10 kW
Rated current (HO)	4.20 A	Filter class (integrated)	Class A
Output		Ambient conditions	
Number of phases	3 AC	Cooling	Internal air cooling
Rated voltage	400 V	Cooling air requirement	0.007 m ³ /s (0.247 ft ³ /s)
Rated current (LO)	5.90 A	Installation altitude	1000 m (3280.84 ft)
Rated current (HO)	4.10 A	Ambient temperature	
Max. output current	8.90 A	Operation LO	-10 ... 40 °C (14 ... 104 °F)
Rated power IEC 400V (LO)	2.20 kW	Operation HO	-10 ... 50 °C (14 ... 122 °F)
Rated power NEC 480V (LO)	3.00 hp	Transport	-25 ... 55 °C (-13 ... 131 °F)
Rated power IEC 400V (HO)	1.50 kW	Storage	-25 ... 55 °C (-13 ... 131 °F)
Rated power NEC 480V (HO)	2.00 hp	Relative humidity	
Pulse frequency	4 kHz	Max. operation	95 % RH, condensation not permitted
Output frequency for vector control	0 ... 200 Hz		
Output frequency for V/f control	0 ... 550 Hz		

Overload capability

Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

SIEMENS


Data sheet for SINAMICS Power Module PM230

MLFB-Ordering data6SL3223-0DE22-2AG1



Mechanical data		Connections	
Degree of protection		Line side	
IP55 / UL type 12			
Size		Version	
FSA		Plug-in screw terminals	
Net weight		Conductor cross-section	
4.30 kg (9.48 lb)		1.00 ... 2.50 mm² (AWG 18 ... AWG 14)	
Width		Motor end	
154 mm (6.06 in)			
Height		Version	
460 mm (18.11 in)		Plug-in screw terminals	
Depth		Conductor cross-section	
249 mm (9.80 in)		1.00 ... 2.50 mm² (AWG 18 ... AWG 14)	

Converter losses to EN 50598-2*	
Efficiency class	IE2
Comparison with the reference converter (90% / 100%)	-70.83 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter without options/components.

*converted values

Max. motor cable length	
Shielded	50 m (164.04 ft)
Unshielded	100 m (328.08 ft)

Standards	
Compliance with standards	UL, CE, C-Tick (RCM)
CE marking	Low-voltage directive 2006/95/EC