



Figure similar

Data sheet for Control Unit Adapter Kit

Article No. : 6SL3255-0BW01-0NA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data	
Operating voltage via	
the Power Module	DC 24 V
Connections ¹⁾	
Design	Pigtail
Cable length	1.5 m
Number of electrical cores	10
Conductor cross-section	0.13 mm² (AWG 26)
Standards	
Compliance with standards	CE, UL, C-Tick (RCM), TÜV, EAC
CE marking	Low-voltage directive 2014/35/EC
Ambient conditions	
Ambient temperature during	
Operation	-10 ... 60 °C (14 ... 140 °F)
Storage	-40 ... 70 °C (-40 ... 158 °F)
Relative humidity during	
Operation max.	95 %

Mechanical data	
Degree of protection	IP20 / UL open type
Power Module Interface Adapter	
Height	166.78 mm (6.57 in)
Width	27.75 mm (1.09 in)
Depth	36.25 mm (1.43 in)
Weight	240 g (0.53 lb)
Control Unit adapter plate	
Height	252.5 mm (9.94 in)
Width	89.2 mm (3.51 in)
Depth	59.5 mm (2.34 in)
Weight	661 g (1.46 lb)

¹⁾The connection cable is connected at one end to the Control Unit adapter plate. The customer has to plug the other end into the Power Module Interface Adapter.