

Data sheet for SINAMICS G120P Cabinet

MLFB-Ordering data: 6SL3710-1PE33-0CA0-Z ** D94+K98+M54+T85

Client order no.:

Order no.:

Offer no.: Remarks:

Item no.:

Consignment no.:

Project:

Rated data

(2Q)

Input Supply frequency 47...63 Hz Supply voltage 400 V ±10% Rated input current 317.0 A Max. current 415 A Pulse number 6

Output:

Energy recovery capability

Output voltage	400 V
Rated power (LO) in kW	160 kW
Rated power (HO) in kW	132 kW
Rated output current	300.0 A
Rated output current (LO)	290 A
Rated output current (HO)	240 A
Output current Max	392 A
Pulse frequency (nominal)	2.00 kHz

Basic data:

Absolute power loss in stand-by	93 W
Sound pressure level L _{pA} (1 m)	63 dB
Conductor cross section, max. (IEC)	2 x 240 mm²
Degree of protection	IP54
Installation envelope dimensions (H x W x	2400 mm x 600 mm x 600 mm
Weight approx.	290 kg
Frame size	FSGX
Design	C (compact)
Color, paint shade	RAL7035
Compliance with standards	CE, RCM, EAC


Environmental conditions

Installation altitude	1000 m
Coolant	Air
Coolant requirement, air	0.21 m³/s
Ambient temperature	0 °C - +40 °C

Converter losses to IEC61800-9-2*

IE2 Efficiency class

Comparison with the reference converter (90% / 100%) 43.7 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard IEC61800-9-2) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter including line choke without options/components.

Special design

D94	Documentation language: English/Russian
K98	Control Unit CU230P-2 HVAC / USS / RS485 / Modbus RTU / BACnet MS/TP
M54	IP54 degree of protection
T85	Rating plate data in English/Russian

*calculated values

^{**}EMC shield rail with PE rail and crane transport aid included in the standard scope of delivery