

product type designation

product description

Indoor fiber optic indoor cable

Glass fiber-optic cable, sold by the meter, unassembled

Indoor Fiber Optic (62.5/125), halogen-free, non-crush, flame-retardant internal fiber-optic cable, Sold by the meter Delivery unit max. 2000 m minimum order quantity 20 m.



suitability for use

Non-crush, halogen-free and flame-retardant cable for indoor installation

version of the assembled FO cable

For assembly with four BFOC connectors

cable designation

I-V(ZN)HH 2x1 G 62,5/125 OM1

optical data

attenuation factor per length

- at 850 nm / maximum
- at 1300 nm / maximum

3.1 dB/km
0.8 dB/km

bandwidth length product

- at 850 nm
- at 1300 nm

200 GHz·m
600 GHz·m

mechanical data

number of fibers / per FOC core

1

number of FO cores / per FOC cable

2

version of the FO conductor fiber

Multimode graded-index fiber 62.5/125 µm, OM 1

design of the FOC core

Solid core, diameter 900 µm

design of the fiber-optic cable

Segmentable inner conductor

outer diameter

- of the optical fibers
- of the optical fiber sheath
- of the FOC core sheath

62.5 µm
125 µm
2.9 mm

symmetrical deviation / of the outer diameter of the FOC core sheath

0.1 mm

width / of cable sheath

6.8 mm

thickness / of cable sheath

3.9 mm

material

- of the fiber-optic cable core
- of the optical fiber sheath
- of the FOC core sheath
- of the fiber-optic cable sheath
- of the strain relief

Quartz glass
Quartz glass
FRNC
FRNC
Aramid fibers

color

- of the FOC core sheath
- of cable sheath

gray
orange

bending radius

- with single bend / minimum permissible
- with multiple bends / minimum permissible

30 mm
50 mm

tensile load

during installation / short-term	800 N
during operation / maximum	200 N
short-term shear force per length	300 N/cm
continuous shear force per length	100 N/cm
weight per length	30 kg/km
ambient conditions	
ambient temperature	
during operation	-20 ... +60 °C
during storage	-25 ... +70 °C
during transport	-25 ... +70 °C
during installation	-5 ... +50 °C
fire behavior	flame-resistant acc. to IEC 60332-1-2 and IEC 60332-3-22 (Cat. A)
class of burning behaviour / according to EN 13501-6	Eca
chemical resistance	
to mineral oil	acc. to IEC 60811-404 with test oil IRM 902 (acc. to ISO 1817), +70 °C, 4 h and +25 °C, 168 h
to grease	not resistant
to water	conditional resistance
radiological resistance / to UV radiation	not resistant
product features, product functions, product components / general	
product feature	
halogen-free	Yes
silicon-free	Yes
product component / rodent protection	No
wire length	
for glass FOC / for 100BaseFX / for Industrial Ethernet / maximum	4000 m
for glass FOC / for 1000BaseSX / for Industrial Ethernet / maximum	350 m
for glass FOC / for 1000BaseLX / for Industrial Ethernet / maximum	550 m
for glass FOC / with PROFIBUS / maximum	3000 m
standards, specifications, approvals	
certificate of suitability	
RoHS conformity	Yes
reference code	
according to IEC 81346-2	WH
according to IEC 81346-2:2019	WHA
further information / internet-Links	
Internet-Link	
to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
to website: Industrial communication	http://www.siemens.com/simatic-net
to website: Industry Mall	https://mall.industry.siemens.com
to website: Information and Download Center	http://www.siemens.com/industry/infocenter
to website: Selection guide for cables and connectors	https://sie.ag/2QdlxcP
to website: Image database	http://automation.siemens.com/bilddb
to website: CAX-Download-Manager	http://www.siemens.com/cax
to website: Industry Online Support	https://support.industry.siemens.com

last modified:

7/7/2022 