



SIMATIC NET,
PROFIBUS M12 CONNECTING CABLE, (ET200),
PREASSEMBLED PB FC TRAILING CABLE WITH 2 M12
CONNECTORS,
B-CODED, 5-PIN, 1.5 M

Cable length 1.5 m

[nicht versorgt: TAK_ABR691_001_000]

Damping ratio per length

• at 9.6 kHz / maximum	0.0030 dB/m
• at 38.4 kHz / maximum	0.0040 dB/m
• at 4 MHz / maximum	0.025 dB/m
• at 16 MHz / maximum	0.049 dB/m

Impedance

• Nominal value	150 Ω
• at 9.6 kHz	270 Ω
• at 38.4 kHz	185 Ω
• for frequency range 3 MHz ... 20 MHz	150 Ω

Relative symmetrical tolerance

• of the surge impedance at 9.6 kHz	10 %
• of the surge impedance at 38.4 kHz	10 %
• of the surge impedance at 3 MHz ... 20 MHz	10 %

Loop resistance per length / maximum

133 Ω /km

Shield resistance per length / maximum

14 Ω /km

Capacity per length / at 1 kHz

28 pF/m

Operating voltage

• RMS value	100 V
-------------	-------

Mechanical data

Number of electrical wires	2
Design of the electrical connection / FastConnect	Yes
Outer diameter	
• of the inner conductor	0.67 mm
• of the wire insulation	2.56 mm
• of the inner sheath of the cable	5.4 mm
• of the cable sheath	8 mm
Symmetrical tolerance of outer diameter / of cable sheath	0.4 mm
Bending radius	
• with single bend / minimum permissible	40 mm
• with multiple bends / minimum permissible	120 mm
Number of bending cycles	3000000
Traction stress / maximum	100 N
Weight per length	77 kg/km

Permitted ambient conditions

Ambient temperature	
• during operating	-40 ... +60 °C
• during storage	-40 ... +60 °C
• during transport	-40 ... +60 °C
• during installation	-40 ... +60 °C

Product properties, functions, components / general

Product feature	
• halogen-free	No
• [not supplied - silicon-free]	Yes

Standards, specifications, approvals

Verification of suitability	
• RoHS conformity	Yes
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Germanische Lloyd (GL)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (NK)	No
• Polski Rejestr Statkow (PRS)	No

letzte Änderung: Jul 17, 2012