




SIMATIC NET,
PROFIBUS ECOFAST HYBRID CABLE,
TRAILING TYPE CABLE WITH 2XCU 0.64 MM AND 4XCU
1.5 SQMM,
NOT PREASSEMBLED PREFERRED LENGTH, 20 M

Acceptability for application

Cable designation

Cable length

Hybrid cable for connection of ECOFAST stations

02Y (ST)C 1 x 2 x 0.65/2.56 - 150 LI LIH-Z 11Y 4 x 1 x 1.5 VI FRNC
20 m

Electrical data

Damping ratio per length

• at 9.6 kHz / maximum	0.0030 dB/m
• at 38.4 kHz / maximum	0.0040 dB/m
• at 4 MHz / maximum	0.025 dB/m
• at 16 MHz / maximum	0.049 dB/m

Impedance

• Nominal value	150 Ω
• at 9.6 kHz	270 Ω
• at 38.4 kHz	185 Ω
• for frequency range 3 MHz ... 20 MHz	150 Ω

Relative symmetrical tolerance

• of the surge impedance at 9.6 kHz	10 %
• of the surge impedance at 38.4 kHz	10 %
• of the surge impedance at 3 MHz ... 20 MHz	10 %

Loop resistance per length / maximum

138 Ω /km

Shield resistance per length / maximum

15 Ω /km

Capacity per length / at 1 kHz

30 pF/m

Operating voltage / RMS value	100 V
Conductor cross section / of the power wires	1.5 mm ²
Continuous current / of the power wires	12 A
Mechanical data	
Design of shield	Overlapped aluminum-clad foil, sheathed in a braided screen of tinned copper wires
Number of electrical wires	6
Design of the electrical connection / FastConnect	No
Outer diameter	
• of the wire insulation	2.56 mm
• of the cable sheath	11 mm
Symmetrical tolerance of outer diameter / of cable sheath	0.3 mm
Material	
• of the wire insulation	PE
• of the cable sheath	PUR
Color	
• of the insulation of data wires	red / green
• of the power wire insulation	Black
• of the cable sheath	Violet
Bending radius	
• with multiple bends / minimum permissible	82.5 mm
Number of bending cycles	5000000
• Note	For use in cable carriers, for 5 million bending cycles with a bending radius of 82.5 mm (7.5x D) and an acceleration of 2.5 m/s ²
Traction stress / maximum	300 N
Weight per length	150 kg/km
Permitted ambient conditions	
Ambient temperature	
• during operating	-40 ... +60 °C
• during storage	-40 ... +60 °C
• during transport	-40 ... +60 °C
• during installation	-40 ... +60 °C
Chemical resistance	
• to mineral oil	Conditional resistance
• to grease	Conditional resistance
Radiological resistance / to UV radiation	resistant
Product properties, functions, components / general	
Product feature	
• halogen-free	Yes
• silicon-free	Yes

Standards, specifications, approvals

UL/ETL listing / with 300 V rating

No

UL/ETL style / with 600 V rating

No

Verification of suitability

- RoHS conformity

Yes

letzte Änderung:

Aug 4, 2014