

Data sheet

6XV1861-3CT15

Product type designation

Product description

PCF Trailing Cable

PCF fiber-optic cable with plastic cladding, preferred length, preassembled

SIMATIC NET PCF TRAILING CABLE, PREASSEMBLED WITH 2X2 BFOC CONNECTORS, INSERTION GUIDE, LENGTH 150 M



Suitability for use	Cable for applications with high mechanical loading, and motion (e.g. trailing cables), no UL approval
Version of the assembled FO cable	Assembled with four BFOC connectors
Cable designation	AT-V(ZN)Y(ZN)11Y 2K 200/230
Wire length	150 m

Optical data

Damping ratio per length	
• at 650 nm / maximum	10 dB/km
• at 660 nm / maximum	10 dB/km
Bandwidth length product	
• at 650 nm	17 GHz·m

Mechanical data

Number of fibers / per FOC core	1
Number of FO cores / per FOC cable	2
Version of the FO conductor fiber	Step index fiber 200/230 µm
Outer diameter	

• of the optical fibers	200 µm
• of the optical fiber sheath	230 µm
• of the FOC core sheath	2.2 mm
Symmetrical deviation / of the outer diameter of the FOC core sheath	0.1 mm
Outer diameter / of the cable	8.8 mm
Symmetrical deviation / of the outer diameter of the line	0.5 mm
Material	
• of the fiber-optic cable core	Quartz glass
• of the optical fiber sheath	Special polymer
• of the FOC core sheath	PVC
• of the fiber-optic cable sheath	PUR
• of the strain relief	Aramid fibers
Color	
• of the FOC core sheath	orange/black
• of cable sheath	green
Bending radius	
• with single bend / minimum permissible	130 mm
• with multiple bends / minimum permissible	175 mm
Number of bending cycles	5000000
Tensile load	
• during installation / short-term	2000 N
• during operation / maximum	800 N
Short-term shear force per length	500 N/cm
Continuous lateral force per length	300 N/cm
Weight per length	85 kg/km

Permitted ambient conditions

Ambient temperature	
• during operation	-25 ... +75 °C
• during storage	-30 ... +75 °C
• during transport	-30 ... +75 °C
• during installation	-5 ... +50 °C
Burning behavior	flame-retardant
Chemical resistance	
• to mineral oil	resistant
• to grease	resistant
Radiological resistance / to UV radiation	resistant
Protection class IP	IP20

Product properties, functions, components / general

Product feature	
• halogen-free	No

• silicon-free	Yes
Product component / Rodent protection	No
Wire length	
• for PCF FOC / for Industrial Ethernet / maximum	100 m
• for PCF FOC / with PROFIBUS / maximum	400 m

Standards, specifications, approvals

Certificate of suitability	
• RoHS conformity	Yes

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified: 11.03.2016