

Product type designation

SIMATIC NET Antenna Connection Cable RSMA/ RSMA

Product description

Male/Female
Connecting cable for SIMATIC NET antennas, preassembled SIMATIC NET, ANTENNA EXTENSION FRNC CABLE FOR IWLAN PREASSEMBLED WITH 2X R-SMA CONNECTORS FOR CABLE EXTENSION OF ANTENNAS ANT 790, EXTENSION CAN BE CONNECTED WITH FURTHER EXTENSION; CABLE DAMPING 2.5 DBI LENGTH: 5 M, OPERATING INSTRUCTIONS GERMAN/ ENGLISH



Figure similar

Suitability for use	For extending an antenna connection cable
Wire length	5 m
Electrical data	
Number of electrical connections	2
Type of electrical connection	RSMA male/female
Transmission frequency	0 ... 6000 MHz
Damping ratio per length	
• at 2.4 GHz / typical	0.53 dB/m
• at 5.2 GHz / typical	0.83 dB/m
• at 5.85 GHz / typical	0.89 dB/m
Return loss / minimum	23 dB
Impedance	
• Rated value	50 Ω
Capacity per length / at 1 kHz	82 pF/m
Relative speed	82 %

Mechanical data	
Design of the shield	Braided shield made of tin-plated copper wires
Outer diameter	
• of inner conductor	1.4 mm
• of dielectric	3.8 mm
• of cable sheath	6.3 mm
Symmetrical tolerance of the outer diameter / of cable sheath	0.2 mm
Thickness / of cable sheath	0.76 mm
Material	
• of inner conductor	Cu
• of dielectric	polyethylene foam
• of cable sheath	FRNC
Color	
• of cable sheath	pastel turquoise
Bending radius	
• with single bend / minimum permissible	32 mm
• with multiple bends / minimum permissible	45 mm
Tensile load / maximum	80 N
Weight per length	75 kg/km
Permitted ambient conditions	
Ambient temperature	
• during operation	-40 ... +80 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
• during installation	-25 ... +80 °C
Chemical resistance	
• to mineral oil	conditional resistance
Radiological resistance / to UV radiation	resistant
Protection class IP	IP68; when plugged in
Product properties, functions, components / general	
Product feature	
• halogen-free	Yes
• silicon-free	Yes
Standards, specifications, approvals	
Certificate of suitability	
• RoHS conformity	Yes
• Fire protection in accordance with EN 45545-2	No
Standard	
• for behavior in fire: flame resistance	UL 1685 (Vertical tray), UL 1581 Sec. 1090 (H)
Further Information / Internet Links	

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

10/12/2016