

product type designation

product description



IE TP Ground Cable 4x2 (AWG 24, Type C)

Shielded TP installation cable (8-core), sold by the meter, unassembled

IE TP ground cable 4x2 underground cable, Cat6a, 8-core, shielded, cable for connection to IE FC RJ45 plug 4x2, AWG24, sold by the meter delivery unit max. 1000 m minimum order quantity 20 m.

suitability for use

Standard cable with rigid cores for fast, permanent installation outdoors and in the ground

cable designation

2YH(ST)CY2Y 4X2X0.5/1.0 BK

electrical data

attenuation factor per length

• at 10 MHz / maximum	0.058 dB/m
• at 100 MHz / maximum	0.191 dB/m
• at 250 MHz / maximum	0.311 dB/m
• at 300 MHz / maximum	0.343 dB/m
• at 500 MHz / maximum	0.453 dB/m

impedance

• at 1 MHz ... 100 MHz	100 Ω
------------------------	-------

near-end crosstalk per length

• at 1 MHz ... 100 MHz	0.453 dB/m
• at 1 MHz ... 250 MHz	0.393 dB/m
• at 1 MHz ... 300 MHz	0.381 dB/m
• at 1 MHz ... 500 MHz	0.348 dB/m

transfer impedance per length / at 10 MHz

20 mΩ/m

loop resistance per length / maximum

190 mΩ/m

insulation resistance coefficient

5000 GΩ·m

operating voltage

• RMS value	80 V
-------------	------

NVP value in percent

66 %

mechanical data

number of electrical cores

8

design of the shield

Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires

type of electrical connection / FastConnect

Yes

core diameter

• of AWG24 insulated conductor	0.51 mm
--------------------------------	---------

outer diameter

• of inner conductor	0.51 mm
• of the wire insulation	1 mm
• of the inner sheath of the cable	6.1 mm
• of cable sheath	10.5 mm
• of cable sheath / note	IE FC standard cable GP 4x2 (diameter 8 mm) with additional PE outer cover (diameter 10.5 mm)

symmetrical tolerance of the outer diameter / of cable

0.5 mm

sheath	
material	
• of the wire insulation • of the inner sheath of the cable • of cable sheath	polyethylene (PE) FRNC PVC
color	
• of the insulation of data wires • of cable sheath	white-blue/blue, white-orange/orange, white-green/green, white-brown/brown green/black
bending radius	
• with single bend / minimum permissible • with multiple bends / minimum permissible	42 mm 84 mm
tensile load / maximum	100 N
weight per length	107 kg/km
ambient conditions	
ambient temperature	
• during operation • during storage • during transport • during installation • note	-40 ... +80 °C -40 ... +80 °C -40 ... +80 °C -40 ... +80 °C In fixed installation -40 °C to 85 °C
class of burning behaviour / according to EN 13501-6	Fca
chemical resistance	
• to water	Resistant
radiological resistance / to UV radiation	resistant
product features, product functions, product components / general	
product feature	
• halogen-free • silicon-free	No Yes
wire length / for Industrial Ethernet	
• with 100BaseTX • with 1000BaseT • for 10GBase T	90 m 90 m 70 m
standards, specifications, approvals	
UL/ETL listing / 300 V Rating	No
UL/ETL style / 600 V Rating	No
certificate of suitability	
• EAC approval • CE marking • RoHS conformity	Yes Yes Yes
product conformity	
• ANSI/TIA-EIA 568-B.2 Cat.5e • IEC 61784-5-2-CP 2/2 (Ethernet/IP)	Yes Yes
standard for structured cabling	Cat6A
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS) • French marine classification society (BV) • Det Norske Veritas (DNV) • Germanische Lloyd (GL) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS)	No No No No No No No
reference code	
• according to IEC 81346-2 • according to IEC 81346-2:2019	WG WGB
further information / internet-Links	
Internet-Link	
• to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall	http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com

- to website: Information and Download Center
- to website: Selection guide for cables and connectors
- to website: Image database
- to website: CAX-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/industry/infocenter>
<https://sie.ag/2QdlxcP>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

10/30/2021 