

EPAK-VMR-1PH-300-24V**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The analogue converters of the EPAK series are characterised by their compact design. The wide range of functions available with this series of analogue converters make them suitable for applications which do not require international approvals.

Properties:

- Safe isolation, conversion and monitoring of your analogue signals
- Configuration of the input and output parameters directly on the device via DIP switches
- No international approvals
- High interference resistance

General ordering data

Order No.	7760054244
Type	EPAK-VMR-1PH-300-24V
GTIN (EAN)	6944169733765
Qty.	1 pc(s).

EPAK-VMR-1PH-300-24V

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	89 mm	Depth (inches)	3.504 inch
Length	100 mm	Length (inches)	3.937 inch
Net weight	80 g	Width	17.5 mm
Width (inches)	0.689 inch		

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-20 °C...60 °C
---------------------	----------------	-----------------------	----------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Input

Input frequency	40...60 Hz	Input resistance, voltage	1 MΩ±5%
Input signal		Input voltage	$U_{₁}$: 30 ... 300 VAC/DC, $U_{₂}$: 6 ... 60 VAC/DC
	DC, AC (sine)		

Output (digital)

Alarm function	Surge voltage, Undervoltage, Hysteresis: 5% U_N (fixed), Alarm delay: 0...10 s	Max. switching voltage, AC	250 V
Max. switching voltage, DC	30 V	Rated switching current	3 A
Type	Relay, 1 CO contact		

General data

Accuracy	Setting tolerance: 5% of U_N , Transmission tolerance: 5% of U_N	Configuration	DIP switch and potentiometer
Galvanic isolation	between input / output / supply / relay	Power consumption	<60 mA @24 VDC, <9 mA @230 VAC
Repeat accuracy	2 % $\cdot U_{\text{rated voltage}}$	Step response time	≤ 200 ms (10...90%)
Temperature coefficient	≤ 250 ppm/K of final value	Type of connection	Screw connection
Voltage supply	18...30 VDC		

Insulation coordination

EMC standards	IEC 61000-6-2, IEC 61000-6-4, EN 61326	Galvanic isolation	between input / output / supply / relay
Impulse withstand voltage	4 kV (1.2/50 μs)	Insulation voltage	2.2 kVAC, 1 min, 50 Hz
Pollution severity	2	Rated voltage	300 V AC _{rms}
Surge voltage category	III		

Connection data

Type of connection	Screw connection	Tightening torque, min.	0.4 Nm
Tightening torque, max.	0.6 Nm	Clamping range, rated connection	2 mm ²
Clamping range, min.	0.5 mm ²	Clamping range, max.	2 mm ²
Wire connection cross section AWG, min.	AWG 30	Wire connection cross section AWG, max.	AWG 14

Creation date March 29, 2021 8:40:46 PM CEST

EPAK-VMR-1PH-300-24V**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Classifications**

ETIM 6.0	EC002654	ETIM 7.0	EC002654
ECLASS 9.0	27-21-01-22	ECLASS 9.1	27-21-01-22
ECLASS 10.0	27-21-01-22	ECLASS 11.0	27-21-01-22

Approvals

Approvals



ROHS

Conform

DownloadsApproval/Certificate/Document of
Conformity[Declaration of Conformity](#)

Engineering Data

[STEP](#)

User Documentation

[Instruction sheet](#)

EPAK-VMR-1PH-300-24V

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

